




Boise Cascade
Engineered Wood Products

WESTERN ENGINEERED WOOD PRODUCTS BUILDER GUIDE

**Introducing the
BCI® 6000 1.8**



BCI® Joists



Some products may not be available in all markets. Contact your Boise Cascade EWP representative for availability.

About Floor Performance

Homeowner's expectations and opinions vary greatly due to the subjective nature of rating a new floor. Communication with the ultimate end user to determine their expectation is critical. **Vibration** is usually the cause of most complaints. Installing lateral bridging may help; however, squeaks may occur if not installed properly. Spacing the joists closer together does little to affect the perception of the floor's performance. The most common methods used to increase the performance and reduce vibration of wood floor systems is to

increase the joist depth, limit joist deflections, glue and screw a thicker, tongue-and-groove subfloor, install the joists vertically plumb with level-bearing supports, and install a direct-attached ceiling to the bottom flanges of the joists.

The floor span tables listed below offer three very different performance options, based on performance requirements of the homeowner.

Joist Depth	BCI® Joist Series	★★★ THREE STAR★★★					★★★★ FOUR STAR★★★★					CAUTION ★ MINIMUM STIFFNESS ALLOWED BY CODE ★ CAUTION				
		Live Load deflection limited to L/480: The common industry and design community standard for residential floor joists, 33% stiffer than L/360 code minimum. However, floor performance may still be an issue in certain applications, especially with 9½" and 11⅞" deep joists without a direct-attached ceiling.														
		12" o.c.	16" o.c.	19.2" o.c.	24" o.c.	32" o.c.	12" o.c.	16" o.c.	19.2" o.c.	24" o.c.	32" o.c.	12" o.c.	16" o.c.	19.2" o.c.	24" o.c.	32" o.c.
9½"	5000 1.7	17'-1"	15'-7"	14'-9"	13'-9"	12'-0"	11'-6"	11'-6"	10'-0"	10'-0"	9'-6"	18'-11"	17'-0"	15'-6"	13'-11"	12'-0"
	6000 1.8	17'-11"	16'-5"	15'-6"	14'-5"	13'-2"	11'-6"	11'-6"	10'-0"	10'-0"	9'-10"	19'-10"	18'-2"	17'-2"	15'-9"	13'-8"
	6500 1.8	18'-5"	16'-10"	15'-11"	14'-10"	13'-6"	11'-6"	11'-6"	10'-0"	10'-0"	10'-0"	20'-5"	18'-8"	17'-8"	16'-5"	14'-3"
11⅞"	5000 1.7	20'-2"	18'-5"	17'-5"	15'-9"	13'-4"	15'-6"	14'-4"	13'-6"	12'-7"	11'-5"	22'-3"	19'-4"	17'-7"	15'-9"	13'-4"
	6000 1.8	21'-3"	19'-5"	18'-4"	17'-1"	14'-10"	15'-6"	15'-1"	14'-3"	13'-3"	12'-0"	23'-6"	21'-6"	20'-0"	17'-11"	14'-10"
	6500 1.8	21'-11"	20'-0"	18'-11"	17'-7"	14'-10"	16'-0"	15'-7"	14'-9"	13'-8"	12'-5"	24'-3"	22'-2"	20'-11"	18'-10"	14'-10"
	60 2.0	23'-3"	21'-3"	20'-1"	18'-8"	16'-4"	18'-0"	16'-7"	15'-7"	14'-6"	13'-2"	25'-9"	23'-6"	22'-3"	20'-9"	16'-4"
14"	90 2.0	26'-3"	23'-11"	22'-6"	20'-11"	19'-1"	19'-0"	18'-7"	17'-6"	16'-2"	14'-8"	29'-0"	26'-6"	25'-0"	23'-3"	19'-4"
	5000 1.7	22'-11"	21'-0"	19'-2"	17'-2"	13'-11"	18'-0"	16'-5"	15'-6"	14'-5"	13'-1"	24'-4"	21'-0"	19'-2"	17'-2"	13'-11"
	6000 1.8	24'-2"	22'-2"	20'-11"	19'-6"	15'-5"	18'-11"	17'-3"	16'-3"	15'-2"	13'-9"	26'-9"	23'-11"	21'-10"	19'-6"	15'-5"
	6500 1.8	24'-10"	22'-9"	21'-5"	20'-0"	15'-5"	19'-5"	17'-9"	16'-8"	15'-6"	14'-1"	27'-6"	25'-1"	22'-11"	20'-6"	15'-5"
16"	60 2.0	26'-5"	24'-2"	22'-9"	21'-3"	16'-4"	20'-8"	18'-10"	17'-9"	16'-5"	14'-11"	29'-3"	26'-8"	25'-3"	21'-10"	16'-4"
	90 2.0	29'-9"	27'-1"	25'-6"	23'-8"	19'-6"	23'-3"	21'-1"	19'-9"	18'-4"	16'-7"	32'-10"	30'-0"	28'-3"	26'-0"	19'-6"
	6000 1.8	26'-9"	24'-5"	23'-1"	20'-10"	15'-9"	20'-11"	19'-1"	18'-0"	16'-9"	15'-2"	29'-6"	25'-6"	23'-4"	20'-10"	15'-9"
	6500 1.8	27'-5"	25'-1"	23'-8"	21'-1"	15'-9"	21'-6"	19'-7"	18'-5"	17'-2"	15'-7"	30'-4"	26'-11"	24'-6"	21'-1"	15'-9"
18"	60 2.0	29'-3"	26'-8"	25'-2"	21'-10"	16'-4"	22'-10"	20'-10"	19'-7"	18'-2"	16'-4"	32'-4"	29'-6"	27'-4"	21'-10"	16'-4"
	90 2.0	32'-11"	29'-11"	28'-2"	26'-2"	19'-7"	25'-8"	23'-4"	21'-11"	20'-3"	18'-4"	36'-4"	33'-2"	31'-3"	26'-2"	19'-7"
	90 2.0	35'-11"	32'-8"	30'-9"	28'-7"	23'-10"	28'-1"	25'-5"	23'-11"	22'-2"	20'-0"	39'-8"	36'-2"	34'-1"	31'-9"	23'-10"
20"	90 2.0	38'-10"	35'-4"	33'-4"	30'-11"	24'-8"	30'-4"	27'-6"	25'-11"	24'-0"	21'-8"	42'-11"	39'-1"	36'-10"	32'-11"	24'-8"

- Table values based on residential floor loads of 40 psf live load and 10 psf dead load (12 psf dead load for BCI® 90 2.0 joists).
- Span values assume 23/32" min plywood/OSB rated sheathing is glued and nailed to joists for composite action (joists spaced at 32" o.c. require sheathing rated for such spacing - 7/8" plywood/OSB).
- Table values represent the most restrictive of simple or multiple span applications.
- Table values are the maximum allowable clear distance between supports.
- Table values assume minimum bearing lengths without web stiffeners for joist depths of 16" inches and less (18" & 20" joists require web stiffeners at all bearing locations).
- Floor tile will increase dead load and may require specific deflection limits, contact Boise Cascade EWP Engineering for further information.
- This table was designed to apply to a broad range of applications. It may be possible to exceed the limitations of this table by analyzing a specific application with the BC CALC® sizing software.

Table of Contents

- Product Profiles, About Floor Performance, BCI® Residential Floor Span Tables 2
- BCI® Floor Framing Details 3
- BCI® Joist Hole Location & Sizing 4
- VERSA-LAM® One Floor Beam Span Tables 5
- VERSA-LAM® Two Floor Beam Span Tables 6
- VERSA-LAM® Roof Header Span Tables 7
- VERSA-LAM® Roof Ridge Beam Span Tables 8

- VERSA-LAM® Roof & One Floor Span Tables 9
- Multiple Member Connectors 10
- BCI® Closest Allowable Nail Spacing 10
- VERSA-LAM® Closest Allowable Nail Spacing 11
- VERSA-LAM® Beam Details 11
- Allowable Holes in VERSA-LAM® Products 11
- Information & Support, Lifetime Guarantee ... Back Cover

Additional floor framing details available with BC FRAMER® software (see page 33 of the Western Specifier Guide)

END BEARING DETAILS

F07

Nail Boise Rimboard to BCI® Joists with 8d nail into each flange. Dimension lumber is not suitable for use as rim board with BCI® Joists.

F07A

Dimension lumber is not suitable for use as rim board with BCI® Joists.

F02

BCI® rim joist.

F01

BCI® Joist blocking.

F27A

Top Flange or Face Mount Joist Hanger
VERSA-LAM®

F52

One 8d nail each side at bearing
1 3/4" minimum bearing length
To limit splitting flange, start nails at least 1 1/2" from end. Nails may need to be driven at an angle to limit splitting of bearing plate.

F08

Solid block all posts from above to bearing below.

F03

BCI® rim joist.
Note: BCI® floor joist must be designed to carry wall above when not stacked over wall below.

INTERMEDIATE BEARING DETAILS

F06

For load bearing wall above (stacked over wall below).

BCI® Joist blocking.

F09

Blocking may be required, consult design professional of record and/or local building official.

Load bearing wall above (stacked over wall below)
1/16"
2x block.

F08

Floor Joist Blocking per IRC 502.7 Required in seismic design categories D_s and higher for floor diaphragm (required for all joist types).

BCI® Joist or Boise Rimboard Blocking.
Nail per local code provisions.

BCI® Joist Slope Cut Reinforcement

Detail below restores original allowable shear/reaction value to cut end of BCI® joist. BCI® Joist shall not be used as a collar or rafter tension tie.

2 x 6 min. rafter. Rafter shall be supported by ridge beam or other upper bearing support

Heel Depth (see table below)
6 min. 12. 16" max. BCI® depth
24"

F10

Joist Hanger
Backer block (minimum 12" wide). Nail with 10-10d nails.
Filler block. Nail with 10-10d nails
Backer block required where top flange joist hanger load exceeds 250 lbs. Install tight to top flange.

F58

Double BCI® Joist Connection

Filler Block (see chart below)
Web-Filler Nailing 12" on-center
Connection valid for all applications. Contact Boise EWP Engineering for specific conditions.

F05

Sheathing or rimboard closure
BCI® Joist blocking required for cantilever.

For load bearing cantilever, see pgs 8 and 9 of the Western Specifier Guide. Uplift on backspan shall be considered in all cantilever designs.

End Wall Bearing	Minimum Heel Depth					
	Roof Pitch					
	6/12	7/12	8/12	9/12	10/12	12/12
2 x 4	4 3/8"	4 5/8"	4 7/8"	4 7/8"	4 7/8"	4 7/8"
2 x 6	3 3/8"	3 5/8"	2 5/8"	2 3/4"	2 5/8"	2 1/4"

LATERAL SUPPORT

- BCI® Joists shall be laterally supported at the ends with hangers, rimboard, BCI® rim joist or blocking panels. BCI® blocking panels or rimboard are required at cantilever supports.
- Blocking may be required at intermediate bearings for floor diaphragm per IRC in high seismic areas, consult local building official.

MINIMUM BEARING LENGTH FOR BCI® JOISTS

- Minimum end bearing: 1 1/2" for BCI® 5000, 6000 & 6500; 1 3/4" for BCI® 60 & 90. 3 1/2" is required at cantilever and intermediate supports.
- Longer bearing lengths allow higher reaction values. Refer to the building code evaluation report or the BC CALC® software.

NAILING REQUIREMENTS

- BCI® rim joist, rim board or closure panel to BCI® joist:
 - Rims or closure panel 1 3/4 inches thick and less: 2-8d nails, one each in the top and bottom flange.
 - BCI® 5000 rim joist: 2-10d box nails, one each in the top and bottom flange.
 - BCI® 6000, 60 rim joist: 2-16d box nails, one each in the top and bottom flange.
 - BCI® 6500, 90 rim joist: Toe-nail top flange to rim joist with 2-10d box nails, one each side of flange.
- BCI® rim joist, rim board or BCI® blocking panel to support:
 - 8d nails at 6 inches on center.
 - When used for shear transfer, follow the building designer's specification.

- BCI® joist to support:

- 2-8d nails, one on each side of the web, placed 1 1/2 inches minimum from the end of the BCI® Joist to limit splitting.

- Sheathing to BCI® joist:

- Prescriptive residential floor sheathing nailing requires 8d common nails @ 6" o.c. on edges and @ 12" o.c. in the field (IRC Table R602.3(1)).
- See closest allowable nail spacing limits on page 24 for floor diaphragm nailing specified at closer spacing than IRC.
- Maximum nail spacing for minimum lateral stability: 18" for BCI® 5000, 24" for larger BCI® joist series.
- 14 gauge staples may be substituted for 8d nails if the staples penetrate at least 1 inch into the joist.
- Wood screws may be acceptable, contact local building official and/or Boise Cascade EWP Engineering for further information.

BACKER AND FILLER BLOCK DIMENSIONS

Series	Backer Block Thickness	Filler Block Thickness
5000 1.7	3/4" or 7/8" wood panels	Two 3/4" wood panels or 2x_
6000 1.8	1 1/8" or two 1/2" wood panels	2x_ + 7/16" or 1/2" wood panel
6500 1.8	1 1/8" or two 3/8" wood panels	2x_ + 5/8" or 3/4" wood panel
60 2.0	1 1/8" or two 1/2" wood panels	2x_ + 7/16" or 1/2" wood panel
90 2.0	2x_ lumber	Double 2x_ lumber

- Cut backer and filler blocks to a maximum depth equal to the web depth minus 1/4" to avoid a forced fit.

BCI® RIM JOISTS AND BCI® BLOCKING

Depth [in]	Series	Vertical Load Capacity	
		No W.S. ⁽¹⁾	W.S. ⁽²⁾
9 1/2"	5000 1.7, 6000 1.8, 6500 1.8	2300	N/A
11 1/2"	5000 1.7, 6000 1.8, 6500 1.8	2150	N/A
	60 2.0, 90 2.0	2500	N/A
14"	5000 1.7, 6000 1.8, 6500 1.8	2000	N/A
	60 2.0, 90 2.0	2400	N/A
16"	6000 1.8, 6500 1.8	1900	2500
	60 2.0, 90 2.0	2300	2700
18"	60 2.0, 90 2.0	N/A	2700
20"	90 2.0	N/A	2700

- No web stiffeners required
 - Web stiffeners required at each end of blocking, values not applicable for rim joists
- N/A: Not applicable

WEB STIFFENER REQUIREMENTS



- See Web Stiffener Requirements on page 9.

PROTECT BCI® JOISTS FROM THE WEATHER

- BCI® Joists are intended only for applications that provide permanent protection from the weather. Bundles of BCI® Joists should be covered and stored off of the ground on stickers.

BCI® Joist Hole Location & Sizing

BCI® Joists are manufactured with 1½" round perforated knockouts in the web at approximately 12" on center



Minimum distance from support, listed in table below, is required for all holes greater than 1½"

MINIMUM DISTANCE (D) FROM ANY SUPPORT TO THE CENTERLINE OF THE HOLE																
Round Hole Diameter [in]		2	3	4	5	6	7	8	8 7/8	10	11	12	13	14	15	
Rectangular Hole Side [in]		-	-	-	3	5	7	-	-	-	-	-	-	-	-	
Any 9 1/2" Joist	Span [ft]	8	1'-0"	1'-1"	1'-8"	2'-4"	2'-11"	3'-7"								
		12	1'-0"	1'-7"	2'-7"	3'-6"	4'-5"	5'-4"								
		16	1'-0"	2'-2"	3'-5"	4'-8"	5'-11"	7'-2"								
Round Hole Diameter [in]		2	3	4	5	6	7	8	8 7/8	10	11	12	13	14	15	
Rectangular Hole Side [in]		-	-	-	2	3	5	7	8	-	-	-	-	-	-	
Any 11 1/4" Joist	Span [ft]	8	1'-0"	1'-1"	1'-6"	2'-0"	2'-5"	2'-11"	3'-5"	3'-10"						
		12	1'-0"	1'-7"	2'-3"	3'-0"	3'-8"	4'-5"	5'-1"	5'-9"						
		16	1'-2"	2'-1"	3'-0"	4'-0"	4'-11"	5'-10"	6'-10"	7'-8"						
		20	1'-5"	2'-7"	3'-10"	5'-0"	6'-2"	7'-4"	8'-6"	9'-7"						
Round Hole Diameter [in]		2	3	4	5	6	7	8	8 7/8	10	11	12	13	14	15	
Rectangular Hole Side [in]		-	-	-	-	2	3	5	6	8	9	-	-	-	-	
Any 14" Joist	Span [ft]	8	1'-0"	1'-1"	1'-2"	1'-2"	1'-6"	1'-11"	2'-4"	2'-9"	3'-3"	3'-8"				
		12	1'-0"	1'-1"	1'-2"	1'-7"	2'-3"	2'-11"	3'-6"	4'-1"	4'-10"	5'-6"				
		16	1'-0"	1'-1"	1'-3"	2'-2"	3'-0"	3'-10"	4'-9"	5'-6"	6'-6"	7'-4"				
		20	1'-0"	1'-1"	1'-7"	2'-8"	3'-9"	4'-10"	5'-11"	6'-10"	8'-1"	9'-2"				
		24	1'-0"	1'-1"	1'-11"	3'-3"	4'-6"	5'-10"	7'-1"	8'-3"	9'-9"	11'-0"				
Round Hole Diameter [in]		2	3	4	5	6	7	8	8 7/8	10	11	12	13	14	15	
Rectangular Hole Side [in]		-	-	-	-	-	2	3	5	6	8	9	10	-	-	
Any 16" Joist	Span [ft]	8	1'-0"	1'-1"	1'-2"	1'-2"	1'-3"	1'-3"	1'-7"	1'-11"	2'-4"	2'-9"	3'-2"	3'-7"		
		12	1'-0"	1'-1"	1'-2"	1'-2"	1'-3"	1'-9"	2'-4"	2'-11"	3'-7"	4'-2"	4'-9"	5'-4"		
		16	1'-0"	1'-1"	1'-2"	1'-2"	1'-7"	2'-5"	3'-2"	3'-10"	4'-9"	5'-7"	6'-4"	7'-2"		
		20	1'-0"	1'-1"	1'-2"	1'-2"	2'-0"	3'-0"	4'-0"	4'-10"	5'-11"	6'-11"	7'-11"	8'-11"		
		24	1'-0"	1'-1"	1'-2"	1'-3"	2'-5"	3'-7"	4'-9"	5'-10"	7'-2"	8'-4"	9'-6"	10'-9"		
Round Hole Diameter [in]		2	3	4	5	6	7	8	8 7/8	10	11	12	13	14	15	
Rectangular Hole Side [in]		-	-	-	-	-	-	2	3	5	6	7	9	10	11	
18" BCI® 90 2.0 Joist	Span [ft]	12	1'-0"	1'-1"	1'-2"	1'-2"	1'-5"	1'-11"	2'-4"	2'-9"	3'-3"	3'-9"	4'-2"	4'-8"	5'-1"	5'-7"
		16	1'-0"	1'-1"	1'-2"	1'-4"	1'-11"	2'-7"	3'-2"	3'-8"	4'-5"	5'-0"	5'-7"	6'-3"	6'-10"	7'-5"
		20	1'-0"	1'-1"	1'-2"	1'-8"	2'-5"	3'-3"	4'-0"	4'-8"	5'-6"	6'-3"	7'-0"	7'-9"	8'-7"	9'-4"
		24	1'-0"	1'-1"	1'-2"	2'-0"	2'-11"	3'-10"	4'-9"	5'-7"	6'-7"	7'-6"	8'-5"	9'-4"	10'-3"	11'-2"
		28	1'-0"	1'-1"	1'-4"	2'-5"	3'-5"	4'-6"	5'-7"	6'-6"	7'-9"	8'-9"	9'-10"	10'-11"	12'-0"	13'-1"
Round Hole Diameter [in]		2	3	4	5	6	7	8	8 7/8	10	11	12	13	14	15	
Rectangular Hole Side [in]		-	-	-	-	-	-	-	2	3	5	6	7	8	10	
20" BCI® 90 2.0 Joist	Span [ft]	12	1'-0"	1'-1"	1'-2"	1'-2"	1'-3"	1'-6"	1'-11"	2'-3"	2'-9"	3'-2"	3'-7"	3'-11"	4'-4"	4'-9"
		16	1'-0"	1'-1"	1'-2"	1'-2"	1'-6"	2'-1"	2'-7"	3'-1"	3'-8"	4'-3"	4'-9"	5'-3"	5'-10"	6'-4"
		20	1'-0"	1'-1"	1'-2"	1'-3"	1'-11"	2'-7"	3'-3"	3'-10"	4'-7"	5'-3"	5'-11"	6'-7"	7'-4"	8'-0"
		24	1'-0"	1'-1"	1'-2"	1'-6"	2'-4"	3'-1"	3'-11"	4'-7"	5'-6"	6'-4"	7'-2"	7'-11"	8'-9"	9'-7"
		28	1'-0"	1'-1"	1'-2"	1'-9"	2'-8"	3'-8"	4'-7"	5'-5"	6'-6"	7'-5"	8'-4"	9'-3"	10'-3"	11'-2"

- Select a table row based on joist depth and the actual joist span rounded up to the nearest table span. Scan across the row to the column headed by the appropriate round hole diameter or rectangular hole side. Use the longest side of a rectangular hole. The table value is the closest that the centerline of the hole may be to the centerline of the nearest support.
- The entire web may be cut out. **DO NOT** cut the flanges. Holes apply to either single or multiple joists in repetitive member conditions.
- For multiple holes, the amount of uncut web between holes must equal at least twice the diameter (or longest side) of the largest hole.
- 1½" round knockouts in the web may be removed by using a short piece of metal pipe and hammer.
- Holes may be positioned vertically anywhere in the web. The joist may be set with the 1½" knockout holes turned either up or down.
- This table was designed to apply to the design conditions covered by tables elsewhere in this publication. Use the BC CALC® software to check other hole sizes or holes under other design conditions. It may be possible to exceed the limitations of this table by analyzing a specific application with the BC CALC® software.

GENERAL NOTES

- Continuous lateral support at the top of the beam is assumed.
- Minimum 3-inch end bearing or see BC CALC® software requirements.
- Bearing length specifications assume bearing across the full width of the beam.
- Uniform loading is assumed for all tables.
- Multiple member beams require proper connection schedules.
- Dry service conditions are assumed.
- It may be possible to exceed the limitations of this table by analyzing a specific application with the BC CALC® software.

Roof Notes (see pages 7, 8 & 9)

- Always use roof live and dead loads that meet or exceed the required design loading.
- No roof load reductions have been taken.
- Table assumes 2'-0" roof overhang.

Ridge Beam (see page 8)

- Deflection is limited to L/240 live load and L/180 total load.
- Table based upon either simple or continuous beam span conditions.


Floor Notes (see pages 5, 6, 9)

- Floor loads are 40 psf live load and 10 psf dead load.
- Deflection is limited to L/360 live load and L/240 total load.
- Table based upon either simple or continuous floor joist spans.
- Tables assume a wall weight of 100 plf (pages 6, 9).
- Interior floor support may vary a maximum of 4 feet from centerline (page 9).

Header (Roof) (see page 7)

- Deflection is limited to L/240 live load and L/180 total load.

One Floor Beam Span Table




Required Beam Depths and Bearing Lengths [in]

VERSA-LAM 2.0 3100

Load Duration %	Floor Load [psf]		Beam Support Spacing [Feet]	Width of Building Segment [feet]																
	Live	Dead		KEY: Beam Breadth [in] X Beam Depth [in] End Support / Intermediate Support Bearing Length Requirements [in]																
				20	24	26	28	30	32	36	40									
100%	40	10	8	3.5 x 7.25	1.5/3	3.5 x 7.25	1.5/3	3.5 x 9.5	1.5/3	3.5 x 9.5	1.5/3	3.5 x 9.5	1.5/4.5	3.5 x 9.5	1.5/4.5	3.5 x 9.5	3/4.5	3.5 x 9.5	3/4.5	
				5.25 x 7.25	1.5/1.5	5.25 x 7.25	1.5/3	5.25 x 7.25	1.5/3	5.25 x 7.25	1.5/3	5.25 x 7.25	1.5/3	5.25 x 7.25	1.5/3	5.25 x 7.25	1.5/3	5.25 x 7.25	1.5/3	5.25 x 9.5
			10	3.5 x 9.5	1.5/3	3.5 x 9.5	1.5/4.5	3.5 x 9.5	1.5/4.5	3.5 x 9.5	1.5/4.5	3.5 x 11.875	3/4.5	3.5 x 11.875	3/4.5	3.5 x 11.875	3/6	3.5 x 11.875	3/6	
				5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/4.5	5.25 x 9.5	1.5/4.5	
			12	3.5 x 11.875	1.5/4.5	3.5 x 11.875	3/4.5	3.5 x 11.875	3/4.5	3.5 x 11.875	3/4.5	3.5 x 11.875	3/6	3.5 x 11.875	3/6	3.5 x 14	3/6	3.5 x 14	3/7.5	
				5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/3	5.25 x 11.875	1.5/3	5.25 x 11.875	1.5/3	5.25 x 11.875	1.5/4.5	5.25 x 11.875	1.5/4.5	5.25 x 11.875	3/4.5	5.25 x 11.875	3/4.5	
			14	3.5 x 11.875	1.5/4.5	3.5 x 14	3/4.5	3.5 x 14	3/6	3.5 x 14	3/6	3.5 x 14	3/6	3.5 x 14	3/6	3.5 x 16	3/7.5	3.5 x 16	3/7.5	
				5.25 x 11.875	1.5/3	5.25 x 11.875	1.5/3	5.25 x 11.875	1.5/4.5	5.25 x 11.875	1.5/4.5	5.25 x 11.875	1.5/4.5	5.25 x 14	3/4.5	5.25 x 14	3/4.5	5.25 x 14	3/6	
	16	3.5 x 14	3/4.5	3.5 x 16	3/6	3.5 x 16	3/6	3.5 x 16	3/6	3.5 x 16	3/7.5	3.5 x 16	3/7.5	3.5 x 18	4.5/9	3.5 x 18	4.5/9			
		5.25 x 11.875	1.5/3	5.25 x 14	1.5/4.5	5.25 x 14	1.5/4.5	5.25 x 14	1.5/4.5	5.25 x 14	3/4.5	5.25 x 14	3/4.5	5.25 x 16	3/6	5.25 x 16	3/6			
	18	3.5 x 16	3/6	3.5 x 16	3/6	3.5 x 18	3/7.5	3.5 x 18	3/7.5	3.5 x 18	3/7.5	3.5 x 18	4.5/9	5.25 x 16	3/6	5.25 x 18	3/7.5			
		5.25 x 14	1.5/4.5	5.25 x 14	3/4.5	5.25 x 16	3/4.5	5.25 x 16	3/4.5	5.25 x 16	3/6	5.25 x 16	3/6	7 x 16	3/4.5	7 x 16	3/6			
	20	3.5 x 18	3/6	3.5 x 18	3/7.5	5.25 x 16	3/6	5.25 x 18	3/6	5.25 x 18	3/6	5.25 x 18	3/6	5.25 x 18	3/7.5	-	-			
		5.25 x 16	1.5/4.5	5.25 x 16	3/4.5	7 x 16	1.5/4.5	7 x 16	1.5/4.5	7 x 16	3/4.5	7 x 16	3/4.5	7 x 16	3/4.5	7 x 18	3/6			

Two Floor Beam Span Tables



Required Beam Depths and Bearing Lengths [in]



VERSA-LAM 2.0 3100

Load Duration %	Floor Load [psf]		Beam Support Spacing [Feet]	Width of Building Segment [feet]																		
	Live	Dead		KEY: Beam Breadth [in] X Beam Depth [in] End Support / Intermediate Support Bearing Length Requirements [in]																		
				20	24	26	28	30	32	36	40											
100%	40	10	8	3.5 x 9.5	3/4.5	3.5 x 11.875	3/6	3.5 x 11.875	3/6	3.5 x 11.875	3/6	3.5 x 11.875	3/7.5	3.5 x 14	3/7.5	3.5 x 14	4.5/9	3.5 x 16	4.5/9			
				5.25 x 9.5	1.5/3	5.25 x 9.5	1.5/4.5	5.25 x 9.5	3/4.5	5.25 x 9.5	3/4.5	5.25 x 9.5	3/4.5	5.25 x 9.5	3/6	5.25 x 11.875	3/6	5.25 x 11.875	3/6	5.25 x 11.875	3/6	
			10	3.5 x 11.875	3/6	3.5 x 14	3/7.5	3.5 x 14	3/7.5	3.5 x 14	3/7.5	3.5 x 14	3/7.5	3.5 x 16	4.5/9	3.5 x 16	4.5/9	3.5 x 18	4.5/10.5	5.25 x 14	3/7.5	
				5.25 x 9.5	1.5/4.5	5.25 x 11.875	3/4.5	5.25 x 11.875	3/6	5.25 x 11.875	3/6	5.25 x 11.875	3/6	5.25 x 11.875	3/6	5.25 x 11.875	3/6	5.25 x 14	3/7.5	7 x 11.875	3/6	
			12	3.5 x 14	3/7.5	3.5 x 16	4.5/9	3.5 x 16	4.5/9	3.5 x 18	4.5/9	3.5 x 18	4.5/9	3.5 x 18	4.5/10.5	5.25 x 14	3/7.5	5.25 x 16	4.5/9	5.25 x 16	4.5/9	
				5.25 x 11.875	3/4.5	5.25 x 11.875	3/6	5.25 x 14	3/6	5.25 x 14	3/6	5.25 x 14	3/7.5	5.25 x 14	3/7.5	7 x 11.875	3/6	7 x 14	3/6	7 x 14	3/7.5	
			14	3.5 x 16	4.5/9	3.5 x 18	4.5/10.5	5.25 x 16	3/7.5	5.25 x 16	3/7.5	5.25 x 16	3/7.5	5.25 x 16	4.5/9	5.25 x 16	4.5/9	5.25 x 18	4.5/10.5	-		
				5.25 x 14	3/6	5.25 x 14	3/7.5	7 x 14	3/6	7 x 14	3/6	7 x 14	3/6	7 x 14	3/6	7 x 14	3/7.5	7 x 16	3/7.5	7 x 16	4.5/9	
			16	3.5 x 18	4.5/9	5.25 x 16	3/7.5	5.25 x 18	4.5/9	5.25 x 18	4.5/9	5.25 x 18	4.5/9	5.25 x 18	4.5/9	-		-		-		
				5.25 x 16	3/6	7 x 16	3/6	7 x 16	3/6	7 x 16	3/6	7 x 16	3/6	7 x 16	3/7.5	7 x 16	3/7.5	7 x 18	4.5/9	7 x 18	4.5/9	
			18	5.25 x 18	3/7.5	5.25 x 18	4.5/9	-		-		-		-		-		-		-		
				7 x 16	3/6	7 x 16	3/6	7 x 18	3/7.5	7 x 18	3/7.5	7 x 18	3/7.5	7 x 18	3/7.5	7 x 18	4.5/9	-		-		
			20	-		-		-		-		-		-		-		-		-		
				7 x 18	3/6	7 x 18	3/7.5	-		-		-		-		-		-		-		

See General Notes on page 5.



Roof Header Span Tables




- Minimum end bearing 3 inches or see BC CALC® software requirement.
- 4.5 inch bearing length required in shaded areas.
- See General Notes on page 5.

Required Beam Depths and Bearing Lengths [in]

VERSA-LAM 2.0 3100

Load Duration %	Roof Load [psf]		Rough Opening [Feet]	Width of Building Segment [feet]										
	Live	Dead		KEY: Beam Breadth [in] X Beam Depth [in]										
				20	24	26	28	30	32	36	40			
125%	20	15	9	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25		
				5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25		
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5		
				5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5		
			16	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875		
				5.25 x 9.5	5.25 x 9.5	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875		
	18	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14				
		5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14				
	20	20	9	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 9.5		
				5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25		
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875	
				5.25 x 7.25	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5		
16			3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14		
			5.25 x 9.5	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875		
18	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 16	3.5 x 16				
	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14				
115%	20	15	9	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25		
				5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25		
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5		
				5.25 x 7.25	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5		
			16	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14		
				5.25 x 9.5	5.25 x 9.5	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875		
		18	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 16	3.5 x 16		
			5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14		
		25	15	9	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 9.5	
					5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	
				12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875
					5.25 x 7.25	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	
	16			3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	
				5.25 x 9.5	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	
	18	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 16	3.5 x 16			
		5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14			
	30	15	9	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 9.5	3.5 x 9.5		
				5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25		
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875	3.5 x 11.875	
				5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5		
			16	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 16	
				5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875		
		18	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18		
			5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14			
40		15	9	3.5 x 7.25	3.5 x 7.25	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5		
				5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25		
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14		
				5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 11.875		
	16		3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18		
			5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14	5.25 x 14			
18	3.5 x 14	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	5.25 x 16				
	5.25 x 11.875	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14					
50	15	9	3.5 x 7.25	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875			
			5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 9.5			
		12	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14			
			5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 11.875	5.25 x 11.875			
		16	3.5 x 14	3.5 x 14	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18			
			5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 16			
18	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	5.25 x 16	5.25 x 16	5.25 x 18					
	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 16	5.25 x 16	7 x 14	7 x 14	7 x 14					

Roof and One Floor Span Tables



Required Beam Depths and Bearing Lengths [in]


VERSA-LAM 2.0 3100

Load Duration %	Roof Load [psf]		Rough Opening [Feet]	Width of Building Segment [feet]									
	Live	Dead		KEY: Beam Breadth [in] X Beam Depth [in]									
				20	24	26	28	30	32	36	40		
125%	20	15	6	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	
			9	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875	
			16	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	
			18	3.5 x 11.875	3.5 x 14	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	
			18	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	
	20	20	6	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18	
			9	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 16	5.25 x 16	
			12	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	5.25 x 18	5.25 x 18	
			16	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16	7 x 16	7 x 16	
			18	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25
			18	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	
115%	20	15	6	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	
			9	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	
			12	3.5 x 11.875	3.5 x 14	3.5 x 11.875	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	
			16	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	
			18	3.5 x 16	3.5 x 18	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	
			18	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 16	5.25 x 16	
	25	15	6	3.5 x 18	5.25 x 16	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	5.25 x 16	5.25 x 18	5.25 x 18	
			9	5.25 x 16	7 x 16	5.25 x 16	5.25 x 16	5.25 x 16	7 x 16	7 x 16	7 x 16	7 x 16	
			12	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	
			16	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	
			18	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875	3.5 x 11.875	
			18	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	
115%	30	15	6	3.5 x 11.875	3.5 x 14	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	
			9	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	
			12	3.5 x 16	3.5 x 18	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18	
			16	5.25 x 14	5.25 x 16	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16	
			18	3.5 x 18	5.25 x 16	3.5 x 18	3.5 x 18	3.5 x 18	5.25 x 16	5.25 x 18	5.25 x 18	5.25 x 18	
			18	5.25 x 16	7 x 16	5.25 x 16	5.25 x 16	5.25 x 16	7 x 16	7 x 16	7 x 16	7 x 16	
	40	15	6	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	3.5 x 7.25	
			9	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	5.25 x 7.25	
			12	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 9.5	3.5 x 11.875	3.5 x 11.875	
			16	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	5.25 x 9.5	
			18	3.5 x 11.875	3.5 x 14	3.5 x 11.875	3.5 x 11.875	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	3.5 x 14	
			18	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	5.25 x 11.875	
50	15	6	3.5 x 16	3.5 x 18	3.5 x 16	3.5 x 16	3.5 x 16	3.5 x 18	3.5 x 18	3.5 x 18	3.5 x 18		
		9	5.25 x 14	5.25 x 16	5.25 x 14	5.25 x 14	5.25 x 14	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16		
		12	3.5 x 18	5.25 x 16	3.5 x 18	3.5 x 18	3.5 x 18	5.25 x 16	5.25 x 16	5.25 x 16	5.25 x 16		
		16	5.25 x 16	7 x 14	5.25 x 16	5.25 x 16	5.25 x 16	7 x 14	7 x 14	7 x 16	7 x 16		
		18	5.25 x 18	5.25 x 18	5.25 x 18	5.25 x 18	5.25 x 18	5.25 x 18	5.25 x 18	5.25 x 20	5.25 x 20		
		18	7 x 16	7 x 16	7 x 16	7 x 16	7 x 16	7 x 16	7 x 16	7 x 18	7 x 18		

• Minimum end bearing 3 inches or see BC CALC® software requirement. • 4.5 inch bearing length required in shaded areas. • See General Notes on page 5.

BCI® Closest Allowable Nail Spacing

Nailing Perpendicular to Glue Lines (Wide Face)



Nailing Parallel to Glue Lines (Narrow Face)

Nail Size	All BCI® Joists			
	Nailing Perpendicular to Glue Line (Wide Face)		Nailing Parallel to Glue Line (Narrow Face)	
	O.C. Spacing [inches]	End of Joist [inches]	O.C. Spacing [inches]	End of Joist [inches]
8d Box	2	1½	4	1½
8d Common	2	1½	4	3
10d & 12d Box	2	1½	4	3
16d Box	2	1½	4	3
10d & 12d Common	3	2	6	4
16d Sinker	3	2	6	4
16d Common	3	2	6	4

- If more than one row of nails is used, the rows must be offset at least ½ inch.
- Simpson Strong-Tie A35 connectors may be attached to the side of BCI® 60 & 90 joist flanges only. Use nails as specified by Simpson Strong-Tie; do not attach connectors on both sides of a flange at the same location.

BCI® Diaphragm Table (1)

BCI® Series	Diaphragm Capacity (2)(3) [lb/ft]	
	Unblocked	Blocked
5000	As permitted for 2x framing in building code	320 lb/ft for 6" o.c. nailing @ panel edges 425 lb/ft for 4" o.c. nailing, staggered, @ panel edges
6000, 6500	As permitted for 3x framing in building code	360 lb/ft for 6" o.c. nailing @ panel edges 480 lb/ft for 4" o.c. nailing, staggered @ panel edges
60, 90	As permitted for 3x framing in building code	As permitted for 3x framing in building code with nail spacing no closer than 3" o.c.

NOTES:

- (1) See table 6 of ICC ESR 1336.
- (2) BCI® joists may be substituted for solid sawn framing in horizontal wood diaphragms as shown in Table 2306.3.1 of the IBC.
- (3) Limits controlled by BCI® closest allowable nail spacing limits.

VERSA-LAM® Multiple Member Connectors

Side-Loaded Applications

Number of Members	Maximum Uniform Side Load [plf]							
	Nailed		½" Dia. Through Bolt(1)			⅝" Dia. Through Bolt(1)		
	2 rows 16d Sinks @ 12" o.c.	3 rows 16d Sinks @ 12" o.c.	2 rows @ 24" o.c. staggered	2 rows @ 12" o.c. staggered	2 rows @ 6" o.c. staggered	2 rows @ 24" o.c. staggered	2 rows @ 12" o.c. staggered	2 rows @ 6" o.c. staggered
1¾" VERSA-LAM® (Depths of 18" and less)								
2	470	705	505	1010	2020	560	1120	2245
3(2)	350	525	375	755	1515	420	840	1685
4(3)	use bolt schedule		335	670	1345	370	745	1495
3½" VERSA-LAM®								
2(3)	use bolt schedule		855	1715	N/A	1125	2250	N/A

1. Design values apply to common bolts that conform to ANSI/ASME standard B18.21-1981 (ASTM A307 Grades A&B, SAE J429 Grades 1 or 2, or higher). A washer not less than a standard cut washer shall be between the wood and the bolt head and between the wood and the nut. The distance from the edge of the beam to the bolt holes must be at least 2" for ½" bolts and 2½" for ⅝" bolts. Bolt holes shall be the same diameter as the bolt.
2. The nail schedules shown apply to both sides of a three member beam.
3. 7" wide beams must be top-loaded or loaded from both sides.

Top-Loaded Applications

For top-loaded beams and beams with side loads with less than those shown:


Plies	Depth	Nailing	Maximum Uniform Load From One Side
(2) 1¾" plies	Depth 11⅞" & less	2 rows 16d box/sinker nails @ 12" o.c.	400 plf
	Depth 14" - 18"	3 rows 16d box/sinker nails @ 12" o.c.	600 plf
(3) 1¾" plies (2)	Depth 11⅞" & less	2 rows 16d box/sinker nails @ 12" o.c.	300 plf
	Depth 14" - 18"	3 rows 16d box/sinker nails @ 12" o.c.	450 plf
(4) 1¾" plies	Depth 18" & less	2 rows ½" bolts @ 24" o.c., staggered	335 plf
(2) 3½" plies	Depth 18" & less	2 rows ½" bolts @ 24" o.c., staggered	855 plf
	Depth 20" - 24"	3 rows ½" bolts @ 24" o.c., staggered every 8"	1285 plf

1. Beams wider than 7" must be designed by the engineer of record.
2. All values in these tables may be increased by 15% for snow-load roofs and by 25% for non-snow load roofs where the building code allows.
3. Use allowable load tables or BC CALC® software to size beams.
4. An equivalent specific gravity of 0.5 may be used when designing specific connections with VERSA-LAM®.
5. Connection values are based upon the 2005 NDS.
6. **FastenMaster TrussLok, Simpson Strong-Tie SDW or SDS, and USP WS screws may also be used to connect multiple member VERSA-LAM® beams, contact Boise EWP Engineering for further information.**

Designing Connections for Multiple VERSA-LAM® Members

When using multiple ply VERSA-LAM® beams to create a wider member, the connection of the plies is as critical as determining the beam size. When side loaded beams are not connected properly, the inside plies do not support their share of the load and thus the load-carrying capacity of the full member decreases significantly. The following is an example of how to size and connect a multiple-ply VERSA-LAM® floor beam.

Given: Beam shown below is supporting residential floor load (40 psf live load, 10 psf dead load) and is spanning 16'-0". Beam depth is limited to 14".




Find: A multiple 1¾" ply VERSA-LAM® that is adequate to support the design loads and the member's proper connection schedule.

1. Calculate the tributary width that beam is supporting:
 $14' / 2 + 18' / 2 = 16'$.
2. Use PLF tables on pages 28-30 of WSG or BC CALC® to size beam.
A Triple VERSA-LAM® 2.0 2800 1¾" x 14" is found to adequately support the design loads.
3. Calculate the maximum plf load from one side (the right side in this case).
 $\text{Max. Side Load} = (18' / 2) \times (40 + 10 \text{ psf}) = 450 \text{ plf}$
4. Go to the Multiple Member Connection Table, Side-Loaded Applications, 1¾" VERSA-LAM®, 3 members
5. The proper connection schedule must have a capacity greater than the max. side load:
Nailed: 3 rows 16d sinks @ 12" o.c.:
525 plf is greater than 450 plf OK
Bolts: ½" diameter 2 rows @ 12" staggered:
755 plf is greater than 450 plf OK

Closest Allowable Nail Spacing

Nailing Parallel to Glue Lines (Narrow Face)



Nailing Perpendicular to Glue Lines (Wide Face)

Nailing Notes

- 1) For 1 1/4" thickness and greater, 2 rows of nails (such as for a metal strap) are allowed (use 1/2" minimum offset between rows and stagger nails).

Nail Size	Nailing Parallel to Glue Lines (Narrow Face) ⁽¹⁾								Nailing Perpendicular to Glue Lines (Wide Face)	
	VERSA-RIM® 1 1/16"		VERSA-LAM® 1.4 1800 Rimboard 1 1/4"		VERSA-LAM® 1 3/4" & 2 5/8"		VERSA-LAM® 3 1/2" & Wider		All Products	
	O.C. [inches]	End [inches]	O.C. [inches]	End [inches]	O.C. [inches]	End [inches]	O.C. [inches]	End [inches]	O.C. [inches]	End [inches]
8d Box	3	1 1/2	3	1 1/2	2	1	2	1/2	2	1/2
8d Common	4	3	3	2	3	2	2	1	2	1
10d & 12d Box	4	3	3	2	3	2	2	1	2	1
16d Box	4	3	3	2	3	2	2	1	2	1
10d & 12d Common	6	4	4	3	4	3	2	2	2	2
16d Sinker	6	4	4	3	4	3	2	2	2	2
16d Common	6	4	6	4	6	3	2	2	2	2

- Offset and stagger nail rows from floor sheathing and wall sole plate.
- Simpson Strong-Tie A35 and LPT4 connectors may be attached to the side VERSA-LAM®/VERSA-RIM®. Use nails as specified by Simpson Strong-Tie.

VERSA-LAM® Beam Details

Bearing at concrete/masonry walls

Provide moisture barrier at support and lateral restraint.

1/2" air space required between concrete and wood.

B01

Bearing for door or window header

Strap per code if top plate is not continuous over header.

Trimmers

B02

Beam to beam connector

Verify hanger capacity with hanger literature

B03

Bearing at column

VERSA-LAM® column

Note: Drilling permitted for standard connectors.

B04

Slope seat cut

Sloped seat cut. Not to exceed inside face of bearing.

Provide adequate lateral support

B06

Bevel cut

DO NOT bevel cut VERSA-LAM® beyond inside face of wall without approval from Boise EWP Engineering or BC CALC® software analysis.

B07

Beam to concrete/masonry walls

Wood top plate must be flush with inside of wall

Hanger

Moisture barrier between concrete and wood

B08

Bearing framing into wall

Strap per code if top plate is not continuous

B09

VERSA-LAM® Installation Notes


- Minimum of 1/2" air space between beam and wall pocket or adequate barrier must be provided between beam and concrete/masonry.
- Adequate bearing shall be provided. If not shown on plans, please refer to load tables in your region's Specifier Guide.
- VERSA-LAM® beams are intended for interior applications only and should be kept as dry as possible during construction.
- Continuous lateral support of top of beam shall be provided (side or top bearing framing).

Allowable Holes in VERSA-LAM® Beams


Notes

1. Square and rectangular holes are not permitted.
2. Round holes may be drilled or cut with a hole saw anywhere within the shaded area of the beam.
3. The horizontal distance between adjacent holes must be at least two times the size of the larger hole.
4. Do not drill more than three access holes in any four foot long section of beam.
5. The maximum round hole diameter permitted is:

Beam Depth	Max. Hole Diameter
5 1/2"	3/4"
7 1/4"	1"
9 1/4" and greater	2"



6. These limitations apply to holes drilled for plumbing or wiring access only. The size and location of holes drilled for fasteners are governed by the provisions of the *National Design Specification® for Wood Construction*.
7. Beams deflect under load. Size holes to provide clearance where required.
8. This hole chart is valid for beams supporting uniform load only. For beams supporting concentrated loads or for beams with larger holes, contact Boise EWP Engineering.



If in doubt ask!
For the number of the closest Boise EWP distributor/support center, call **1-800-232-0788**

- Expert help is just a phone call away
- Effective and comprehensive sales/technical literature
- Training for you and your builder customers
- Easy to use design software
- Aggressive advertising and promotion programs
- FREE builder-oriented video demonstrating proper installation

Boise Cascade has a proven track record of providing quality wood products and a nationwide building materials distribution network for our customers, helping them to enhance their own businesses.

Boise Engineered Wood Products build better homes with stronger, stiffer floors using only wood purchased in compliance with Sustainable Forestry Initiative (SFI) programs. Take a moment to view our green brochure at http://www.bc.com/wood/ewp/Boise_EWP_Green.html.

BOISE CASCADE IS CERTIFIED BY SFI, AMERICA'S LEADING FORESTRY CERTIFICATION PROGRAM:

Boise Cascade doesn't own forests, but buys wood fiber in compliance with SFI, the Sustainable Forestry Initiative®, which certifies the dominant share of North American forest acreage -- 160+ million acres. Boise Cascade is an SFI chain-of-custody certified national supplier. Chain-of-custody tracks and records possession and transfer of wood fiber from forest of origin through all stages of distribution and production to the homebuilder. Chain-of-custody assures that Boise Cascade products are made using fiber from responsibly-managed forests and not from areas that are illegally harvested, major tropical wilderness areas or biodiversity hotspots. Boise Cascade's computerized chain-of-custody system documents sourcing of all wood fiber purchased, ensuring that none gets into Boise Cascade inventory unless it comes from acceptable sources.



Lifetime Guaranteed Quality and Performance

Boise Cascade warrants its BCI® Joist, VERSA-LAM®, and ALLJOIST® products to comply with our specifications, to be free from defects in material and workmanship, and to meet or exceed our performance specifications for the normal and expected life of the structure when correctly stored, installed and used according to our Installation Guide.

BCI® Joists, VERSA-LAM® and ALLJOIST® must be stored, installed and used in accordance with this Installation Guide, building codes and to the extent not inconsistent with this Installation Guide, usual and customary building practices and standards. VERSA-LAM®, ALLJOIST® and BCI® Joists must be wrapped, covered and stored off of the ground on stickers at all times prior to installation. VERSA-LAM®, ALLJOIST® and BCI® Joists are intended only for applications that assure no exposure to weather or the elements and an environment that is free from moisture from any source, or any pest, organism or substance which degrades or damages wood or glue bonds. Failure to correctly store, use or install VERSA-LAM®, ALLJOIST®, and BCI® Joist in accordance with this Installation Guide will void the limited warranty.

For information about Boise's engineered wood products, including sales terms and conditions, warranties and disclaimers, visit our website at www.BC.com/ewp

BCI, BC CALC, BC FRAMER, BC RIM BOARD, BOISE GLULAM, SIMPLE FRAMING SYSTEM, VERSA-LAM, VERSA-RIM, VERSA-STRAND, and VERSA-STUD are trademarks of Boise Cascade, L.L.C. or its affiliates.

Your Dealer is:

If no dealer is listed, call 1-800-232-0788



Boise Cascade
Engineered Wood Products