Unit and Rough Opening Sizing

Single or M.E.U. 6/6, 6/8, 7/0, 8/0

Single or M.E.U. - Inswing

Brickmould Dim.	28"	32"	34"	36"	38"	40"	46"
Rough Opening	26 1/4"	30 1/4"	32 1/4"	34 1/4"	36 1/4"	38 1/4"	44 1/4"
Unit Dimension	25 1/2"	29 1/2"	31 1/2"	33 1/2"	35 1/2"	37 1/2"	43 1/2"

Brickmould Dim. (Inswing)	Rough Opening (Inswing)	Unit Dimension (Inswing)	Height	Door sizes							Unit Dim. Composite (Outswing)	Unit Dim. Aluminum (Outswing)	Rough Opening Composite (Outswing)	Rough Opening Aluminum (Outswing)	Brickmould Dim. Composite (Outswing)	Brickmould Dim. Aluminum (Outswing)
80 1/2"	79 3/4"	79 1/4"	6/6	2/0	2/4	2/6	2/8	2/10	3/0	3/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
82 7/8"	82"	81 5/8"	6/8	2/0	2/4	2/6	2/8	2/10	3/0	3/6	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
86 7/8"	86"	85 5/8"	7/0	2/0	2/4	2/6	2/8	2/10	3/0	3/6	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
98 7/8"	98"	97 5/8"	8/0	2/0	2/4	2/6	2/8	2/10	3/0	3/6	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Unit Dim.	25 1/2"	29 1/2"	31 1/2"	33 1/2"	35 1/2"	37 1/2"	43 1/2"
Rough Opening	26 1/4"	30 1/4"	32 1/4"	34 1/4"	36 1/4"	38 1/4"	44 1/4"
Brickmould Dim.	28 1/2"	32 1/2"	34 1/2"	36 1/2"	38 1/2"	40 1/2"	46 1/2"

Single or M.E.U. - Outswing

For M.E.U., add actual unit dimension to door rough opening width for total rough opening width.

For units with public access sills, subtract 13/16" from inswing height. Unit widths will be the same as in the table above.

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



F L R

Outswing



F L R

Unit and Rough Opening Sizing

THERMA-TRU DOORS

French - 7/8" Astragal, 6/6, 6/8, 7/0, 8/0

French - Inswing - Astragal

	4/0	4/8	5/0	5/4	5/8	6/0
Brickmould Dim.	52 11/16"	60 11/16"	64 11/16"	68 11/16"	72 11/16"	76 11/16"
Rough Opening	50 15/16"	58 15/16"	62 15/16"	66 15/16"	70 15/16"	74 15/16"
Unit Dimension	50 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	74 3/16"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



French - Outswing - Astragal

	4/0	4/8	5/0	5/4	5/8	6/0
Unit Dim.	50 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	74 3/16"
Rough Opening	50 15/16"	58 15/16"	62 15/16"	66 15/16"	70 15/16"	74 15/16"
Brickmould Dim.	53 3/16"	61 3/16"	65 3/16"	69 3/16"	73 3/16"	77 3/16"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For units with public access sills, subtract 13/16" from inswing height. Unit widths will be the same as in the table above.

Hand Designations (Viewed from the exterior)	
A	Astragal (Passive)
L	Left Hand
R	Right Hand

Inswing



LA



AR

Outswing



AL



RA

Unit and Rough Opening Sizing

Double - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Double - Inswing - Standard Mullion

Brickmould Dim.	53"	61"	65"	69"	73"	77"
Rough Opening	51 1/4"	59 1/4"	63 1/4"	67 1/4"	71 1/4"	75 1/4"
Unit Dimension	50 1/2"	58 1/2"	62 1/2"	66 1/2"	70 1/2"	74 1/2"



Double - Outswing - Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FF LF RF FL FR

Outswing

FF LF RF FL FR

Unit and Rough Opening Sizing

THERMA TRU DOORS

Double - Wide Mullion - 6/6, 6/8, 7/0, 8/0

Double - Inswing - Wide Mullion

Brickmould Dim.	53 1/2"	61 1/2"	65 1/2"	69 1/2"	73 1/2"	77 1/2"
Rough Opening	51 3/4"	59 3/4"	63 3/4"	67 3/4"	71 3/4"	75 3/4"
Unit Dimension	51"	59"	63"	67"	71"	75"



Unit Dim.	51"	59"	63"	67"	71"	75"
Rough Opening	51 3/4"	59 3/4"	63 3/4"	67 3/4"	71 3/4"	75 3/4"
Brickmould Dim.	54"	62"	66"	70"	74"	78"

Double - Outswing - Wide Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FF LF RF FL FR

Outswing

FF LF RF FL FR

Triple - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Triple - Inswing - Standard Mullion

Brickmould Dim.	78"	90"	96"	102"	108"	114"
Rough Opening	76 1/4"	88 1/4"	94 1/4"	100 1/4"	106 1/4"	112 1/4"
Unit Dimension	75 1/2"	87 1/2"	93 1/2"	99 1/2"	105 1/2"	111 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Triple - Outswing - Standard Mullion

Unit Dim.	75 1/2"	87 1/2"	93 1/2"	99 1/2"	105 1/2"	111 1/2"
Rough Opening	76 1/4"	88 1/4"	94 1/4"	100 1/4"	106 1/4"	112 1/4"
Brickmould Dim.	78 1/2"	90 1/2"	96 1/2"	102 1/2"	108 1/2"	114 1/2"

Height	Unit Dim. (Composite)	Rough Opening (Composite)	Brickmould Dim. (Composite)
6/6	78 5/8"	79 1/8"	80 1/8"
6/8	80 15/16"	81 7/16"	82 7/16"
7/0	84 15/16"	85 7/16"	86 7/16"
8/0	96 15/16"	97 7/16"	98 7/16"

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

Triple - Wide Mullion - 6/6, 6/8, 7/0, 8/0

Triple - Inswing - Wide Mullion

Brickmould Dim.	79"	91"	97"	103"	109"	115"
Rough Opening	77 1/4"	89 1/4"	95 1/4"	101 1/4"	107 1/4"	113 1/4"
Unit Dimension	76 1/2"	88 1/2"	94 1/2"	100 1/2"	106 1/2"	112 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Triple - Outswing - Wide Mullion

Unit Dim.	76 1/2"	88 1/2"	94 1/2"	100 1/2"	106 1/2"	112 1/2"
Rough Opening	77 1/4"	89 1/4"	95 1/4"	101 1/4"	107 1/4"	113 1/4"
Brickmould Dim.	79 1/2"	91 1/2"	97 1/2"	103 1/2"	109 1/2"	115 1/2"

Height	Unit Dim. (Composite)	Rough Opening (Composite)	Brickmould Dim. (Composite)
6/6	78 5/8"	79 1/8"	80 1/8"
6/8	80 15/16"	81 7/16"	82 7/16"
7/0	84 15/16"	85 7/16"	86 7/16"
8/0	96 15/16"	97 7/16"	98 7/16"

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

Single - Continuous with 10" Sidelite - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Standard Mullion

		Brickmould Dim.	43"	45"	47"	49"	51"	57"				
		Rough Opening	41 1/4"	43 1/4"	45 1/4"	47 1/4"	49 1/4"	55 1/4"				
		Unit Dimension	40 1/2"	42 1/2"	44 1/2"	46 1/2"	48 1/2"	54 1/2"				
80 1/2"	79 3/4"	79 1/4"	6/6	2/4	2/6	2/8	2/10	3/0	3/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
82 7/8"	82"	81 5/8"	6/8	2/4	2/6	2/8	2/10	3/0	3/6	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
86 7/8"	86"	85 5/8"	7/0	2/4	2/6	2/8	2/10	3/0	3/6	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
98 7/8"	98"	97 5/8"	8/0	2/4	2/6	2/8	2/10	3/0	3/6	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"
										Composite	Aluminum	Composite	Aluminum	Composite	Aluminum
				40 1/2"	42 1/2"	44 1/2"	46 1/2"	48 1/2"	54 1/2"	Unit Dim.					
				41 1/4"	43 1/4"	45 1/4"	47 1/4"	49 1/4"	55 1/4"	Rough Opening					
				43 1/2"	45 1/2"	47 1/2"	49 1/2"	51 1/2"	57 1/2"	Brickmould Dim.					

Single with 1 Sidelite - Outswing - Continuous Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

LF RF FL FR

Outswing



LF RF FL FR

Unit and Rough Opening Sizing

THERMA TRU DOORS

Single - Continuous with 12" Sidelite - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Standard Mullion

Brickmould Dim.	45"	47"	49"	51"	53"	59"
Rough Opening	43 1/4"	45 1/4"	47 1/4"	49 1/4"	51 1/4"	57 1/4"
Unit Dimension	42 1/2"	44 1/2"	46 1/2"	48 1/2"	50 1/2"	56 1/2"



42 1/2"	44 1/2"	46 1/2"	48 1/2"	50 1/2"	56 1/2"	Unit Dim.	
43 1/4"	45 1/4"	47 1/4"	49 1/4"	51 1/4"	57 1/4"	Rough Opening	
45 1/2"	47 1/2"	49 1/2"	51 1/2"	53 1/2"	59 1/2"	Brickmould Dim.	

Single with 1 Sidelite - Outswing - Continuous Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

Outswing



Single - Continuous with 14" Sidelite - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Standard Mullion

Door Height	Brickmould Dim. (height)	Rough Opening (height)	Unit Dimension (height)	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim. (width)				47"	49"	51"	53"	55"	61"
Rough Opening (width)				45 1/4"	47 1/4"	49 1/4"	51 1/4"	53 1/4"	59 1/4"
Unit Dimension (width)				44 1/2"	46 1/2"	48 1/2"	50 1/2"	52 1/2"	58 1/2"
6/6	80 1/2"	79 3/4"	79 1/4"						
6/8	82 7/8"	82"	81 5/8"						
7/0	86 7/8"	86"	85 5/8"						
8/0	98 7/8"	98"	97 5/8"						



Single with 1 Sidelite - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	44 1/2"	46 1/2"	48 1/2"	50 1/2"	52 1/2"	58 1/2"
Rough Opening	45 1/4"	47 1/4"	49 1/4"	51 1/4"	53 1/4"	59 1/4"
Brickmould Dim.	47 1/2"	49 1/2"	51 1/2"	53 1/2"	55 1/2"	61 1/2"

Door Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



LF RF FL FR

Outswing



LF RF FL FR

Unit and Rough Opening Sizing

Single - Continuous with 2-10" Sidelites - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	54"	56"	58"	60"	62"	68"
Rough Opening	52 1/4"	54 1/4"	56 1/4"	58 1/4"	60 1/4"	66 1/4"
Unit Dimension	51 1/2"	53 1/2"	55 1/2"	57 1/2"	59 1/2"	65 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	51 1/2"	53 1/2"	55 1/2"	57 1/2"	59 1/2"	65 1/2"
Rough Opening	52 1/4"	54 1/4"	56 1/4"	58 1/4"	60 1/4"	66 1/4"
Brickmould Dim.	54 1/2"	56 1/2"	58 1/2"	60 1/2"	62 1/2"	68 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



FLF FRF

Outswing



FLF FRF

Unit and Rough Opening Sizing

Single - Continuous with 2-12" Sidelites - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	58"	60"	62"	64"	66"	72"
Rough Opening	56 1/4"	58 1/4"	60 1/4"	62 1/4"	64 1/4"	70 1/4"
Unit Dimension	55 1/2"	57 1/2"	59 1/2"	61 1/2"	63 1/2"	69 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"

Single with 2 Sidelites - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	55 1/2"	57 1/2"	59 1/2"	61 1/2"	63 1/2"	69 1/2"
Rough Opening	56 1/4"	58 1/4"	60 1/4"	62 1/4"	64 1/4"	70 1/4"
Brickmould Dim.	58 1/2"	60 1/2"	62 1/2"	64 1/2"	66 1/2"	72 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single - Continuous with 2-14" Sidelites - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	62"	64"	66"	68"	70"	76"
Rough Opening	60 1/4"	62 1/4"	64 1/4"	66 1/4"	68 1/4"	74 1/4"
Unit Dimension	59 1/2"	61 1/2"	63 1/2"	65 1/2"	67 1/2"	73 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	59 1/2"	61 1/2"	63 1/2"	65 1/2"	67 1/2"	73 1/2"
Rough Opening	60 1/4"	62 1/4"	64 1/4"	66 1/4"	68 1/4"	74 1/4"
Brickmould Dim.	62 1/2"	64 1/2"	66 1/2"	68 1/2"	70 1/2"	76 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



FLF FRF

Outswing



FLF FRF

Single with 10" Sidelite - Continuous Mullion Wide or Boxed - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Wide Mullion or Boxed

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	43 1/2"	45 1/2"	47 1/2"	49 1/2"	51 1/2"	57 1/2"
Rough Opening	41 3/4"	43 3/4"	45 3/4"	47 3/4"	49 3/4"	55 3/4"
Unit Dimension	41"	43"	45"	47"	49"	55"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"

Single with 1 Sidelite - Outswing - Continuous Wide Mullion or Boxed

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	41"	43"	45"	47"	49"	55"
Rough Opening	41 3/4"	43 3/4"	45 3/4"	47 3/4"	49 3/4"	55 3/4"
Brickmould Dim.	44"	46"	48"	50"	52"	58"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations:
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with one 10" sidelite and one mullion spread 3/4" would be:
49" unit size + 3/4" spread = 49 3/4"
Units can be spread 0" to 3" in 1/4" increments.
Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

THERMA TRU DOORS

Single with 12" Sidelite - Continuous Wide Mullion or Boxed - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Wide Mullion or Boxed

Brickmould Dim.		45 1/2"	47 1/2"	49 1/2"	51 1/2"	53 1/2"	59 1/2"
	Rough Opening	43 3/4"	45 3/4"	47 3/4"	49 3/4"	51 3/4"	57 3/4"
	Unit Dimension	43"	45"	47"	49"	51"	57"
80 1/2"	79 3/4"	79 1/4"	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
82 7/8"	82"	81 5/8"	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
86 7/8"	86"	85 5/8"	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
98 7/8"	98"	97 5/8"	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"
			Composite	Aluminum	Composite	Aluminum	Composite	Aluminum



Unit Dim.	43"	45"	47"	49"	51"	57"	
Rough Opening	43 3/4"	45 3/4"	47 3/4"	49 3/4"	51 3/4"	57 3/4"	
Brickmould Dim.	46"	48"	50"	52"	54"	60"	

Single with 1 Sidelite - Outswing - Continuous Wide Mullion or Boxed

For Spread Mullion Configurations:
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with one 12" sidelite and one mullion spread 3/4" would be:
51" unit size + 3/4" spread = 51 3/4"
Units can be spread 0" to 3" in 1/4" increments.
Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

LF RF FL FR

Outswing



LF RF FL FR

Single with 14" Sidelite - Continuous Wide Mullion or Boxed - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Wide Mullion or Boxed

Brickmould Dim.		47 1/2"	49 1/2"	51 1/2"	53 1/2"	55 1/2"	61 1/2"
	Rough Opening	45 3/4"	47 3/4"	49 3/4"	51 3/4"	53 3/4"	59 3/4"
	Unit Dimension	45"	47"	49"	51"	53"	59"
80 1/2"	79 3/4"	79 1/4"	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
82 7/8"	82"	81 5/8"	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
86 7/8"	86"	85 5/8"	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
98 7/8"	98"	97 5/8"	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"
			Composite	Aluminum	Composite	Aluminum	Composite	Aluminum



Unit Dim.	45"	47"	49"	51"	53"	59"	
Rough Opening	45 3/4"	47 3/4"	49 3/4"	51 3/4"	53 3/4"	59 3/4"	
Brickmould Dim.	48"	50"	52"	54"	56"	62"	

Single with 1 Sidelite - Outswing - Continuous Wide Mullion or Boxed

For Spread Mullion Configurations:
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with one 14" sidelite and one mullion spread 3/4" would be:
53" unit size + 3/4" spread = 53 3/4"
Units can be spread 0" to 3" in 1/4" increments.
Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

LF RF FL FR

Outswing



LF RF FL FR

Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single with 2-10" Sidelites - Continuous Wide Mullion or Boxed - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Wide Mullion or Boxed

Door Width	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	55"	57"	59"	61"	63"	69"
Rough Opening	53 1/4"	55 1/4"	57 1/4"	59 1/4"	61 1/4"	67 1/4"
Unit Dimension	52 1/2"	54 1/2"	56 1/2"	58 1/2"	60 1/2"	66 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Continuous Wide Mullion or Boxed

Door Width	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	52 1/2"	54 1/2"	56 1/2"	58 1/2"	60 1/2"	66 1/2"
Rough Opening	53 1/4"	55 1/4"	57 1/4"	59 1/4"	61 1/4"	67 1/4"
Brickmould Dim.	55 1/2"	57 1/2"	59 1/2"	61 1/2"	63 1/2"	69 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations:

Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with two 10" sidelites and two mullions spread 3/4" each would be:

60 1/2" unit size + 3/4" spread + 3/4" spread = 62"

Units can be spread 0" to 3" per mullion in 1/4" increments (0" to 6" per unit in 1/2" increments).

Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Single with 2-12" Sidelites - Continuous Wide Mullion or Boxed - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Wide Mullion or Boxed

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	59"	61"	63"	65"	67"	73"
Rough Opening	57 1/4"	59 1/4"	61 1/4"	63 1/4"	65 1/4"	71 1/4"
Unit Dimension	56 1/2"	58 1/2"	60 1/2"	62 1/2"	64 1/2"	70 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Continuous Wide Mullion or Boxed

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	56 1/2"	58 1/2"	60 1/2"	62 1/2"	64 1/2"	70 1/2"
Rough Opening	57 1/4"	59 1/4"	61 1/4"	63 1/4"	65 1/4"	71 1/4"
Brickmould Dim.	59 1/2"	61 1/2"	63 1/2"	65 1/2"	67 1/2"	73 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations:

Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with two 12" sidelites and two mullions spread 3/4" each would be:

64 1/2" unit size + 3/4" spread + 3/4" spread = 66"

Units can be spread 0" to 3" per mullion in 1/4" increments (0" to 6" per unit in 1/2" increments).

Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single with 2-14" Sidelites - Continuous Wide Mullion or Boxed - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Wide Mullion or Boxed

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	63"	65"	67"	69"	71"	77"
Rough Opening	61 1/4"	63 1/4"	65 1/4"	67 1/4"	69 1/4"	75 1/4"
Unit Dimension	60 1/2"	62 1/2"	64 1/2"	66 1/2"	68 1/2"	74 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Continuous Wide Mullion or Boxed

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	60 1/2"	62 1/2"	64 1/2"	66 1/2"	68 1/2"	74 1/2"
Rough Opening	61 1/4"	63 1/4"	65 1/4"	67 1/4"	69 1/4"	75 1/4"
Brickmould Dim.	63 1/2"	65 1/2"	67 1/2"	69 1/2"	71 1/2"	77 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations:
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with two 14" sidelites and two mullions spread 3/4" each would be:
68 1/2" unit size + 3/4" spread + 3/4" spread = 70"
Units can be spread 0" to 3" per mullion in 1/4" increments (0" to 6" per unit in 1/2" increments).
Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



FLF FRF

Outswing



FLF FRF

French - Continuous with 2-10" Sidelites - Wide Mullion - 6/6, 6/8, 8/0

French with Continuous Sidelites - Inswing - Wide Mullion

Brickmould Dim.		99 11/16"
	Rough Opening	97 15/16"
		Unit Dimension 97 3/16"

80 1/2"	79 3/4"	79 1/4"	6/6
82 7/8"	82"	81 5/8"	6/8
86 7/8"	86"	85 5/8"	7/0
98 7/8"	98"	97 5/8"	8/0



6/0



6/0



6/0



6/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
F	Fixed Sidelite

Inswing



FLAF



FARF

Unit and Rough Opening Sizing

THERMA-TRU DOORS

French - Continuous with 2-12" Sidelites - Wide Mullion - 6/6, 6/8, 8/0

French with Continuous Sidelites - Inswing - Wide Mullion

Brickmould Dim.		103 11/16"
	Rough Opening	101 15/16"
		Unit Dimension 101 3/16"

80 1/2"	79 3/4"	79 1/4"
82 7/8"	82"	81 5/8"
86 7/8"	86"	85 5/8"
98 7/8"	98"	97 5/8"

6/6



6/0

6/8



6/0

7/0



6/0

8/0



6/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
F	Fixed Sidelite

Inswing



FLAF



FARF

French - Continuous with 2-14" Sidelites - Wide Mullion - 6/6, 6/8, 8/0

French with Continuous Sidelites - Inswing - Wide Mullion

Brickmould Dim.		107 11/16"
	Rough Opening	105 15/16"
		Unit Dimension 105 3/16"

80 1/2"	79 3/4"	79 1/4"
82 7/8"	82"	81 5/8"
86 7/8"	86"	85 5/8"
98 7/8"	98"	97 5/8"

6/6



6/0

6/8



6/0

7/0



6/0

8/0



6/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
F	Fixed Sidelite

Inswing



FLAF



FARF

Unit and Rough Opening Sizing

THERMA TRU DOORS

Sidelite 6/6, 6/8, 7/0, 8/0

Sidelite - Inswing

Rough Opening		*	*	*			
	Unit Dimension	11 1/2"	13 1/2"	15 1/2"			
80"	79 1/2"	6/6 10"	6/6 12"	6/6 14"	78 5/8"	78 1/16"	79 1/8"	78 9/16"
82 1/2"	82"	6/8 10"	6/8 12"	6/8 14"	81 3/16"	80 5/8"	81 11/16"	81 1/8"
86 1/2"	86"	7/0 10"	7/0 12"	7/0 14"	85 3/16"	84 5/8"	85 11/16"	85 1/8"
98 1/2"	98"	8/0 10"	8/0 12"	8/0 14"	97 3/16"	96 5/8"	97 11/16"	97 1/8"
					Composite	Aluminum	Composite	Aluminum
		11 1/2"	13 1/2"	15 1/2"	Unit Dim.			
		*	*	*	Rough Opening			

Sidelite - Outswing

*Add actual unit dimension to door rough opening width for total rough opening width.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel

Inswing

F

Outswing

F

Single with 12" Venting Sidelite - Wide Mullion - 6/6, 6/8, 8/0

Single with Venting Sidelite - Wide Mullion

Brickmould Dim.			45 3/4"	47 3/4"	49 3/4"	51 3/4"	53 3/4"
	Rough Opening		44"	46"	48"	50"	52"
		Unit Dimension	43 1/4"	45 1/4"	47 1/4"	49 1/4"	51 1/4"
80 1/2"	79 3/4"	79 1/4"	6/6				
			2/4	2/6	2/8	2/10	3/0
82 7/8"	82"	81 5/8"	6/8				
			2/4	2/6	2/8	2/10	3/0
98 7/8"	98"	97 5/8"	8/0				
			2/4	2/6	2/8	2/10	3/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
S	Vented Sidelite (hinged off jamb)

Inswing

SL SR LS RS

Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single with 14" Venting Sidelite - Wide Mullion - 6/6, 6/8, 8/0

Single with Venting Sidelite - Wide Mullion

Brickmould Dim.	47 3/4"	49 3/4"	51 3/4"	53 3/4"	55 3/4"
Rough Opening	46"	48"	50"	52"	54"
Unit Dimension	45 1/4"	47 1/4"	49 1/4"	51 1/4"	53 1/4"
80 1/2" / 79 3/4" / 79 1/4"					
82 7/8" / 82" / 81 5/8"					
98 7/8" / 98" / 97 5/8"					



*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
S	Vented Sidelite (hinged off jamb)

Inswing

Single with 2-12" Venting Sidelites - Wide Mullion - 6/6, 6/8, 8/0

Single with Venting Sidelites - Wide Mullion

Brickmould Dim.	59 7/16"	61 7/16"	63 7/16"	65 7/16"	67 7/16"
Rough Opening	57 11/16"	59 11/16"	61 11/16"	63 11/16"	65 11/16"
Unit Dimension	56 15/16"	58 15/16"	60 15/16"	62 15/16"	64 15/16"

80 1/2" / 79 3/4" / 79 1/4"	6/6	2/4	2/6	2/8	2/10	3/0
82 7/8" / 82" / 81 5/8"	6/8	2/4	2/6	2/8	2/10	3/0
98 7/8" / 98" / 97 5/8"	8/0	2/4	2/6	2/8	2/10	3/0

*Outswing not available.

Hand Designations
(Viewed from the exterior)

L	Left Hand
R	Right Hand
S	Sidelite

Inswing



SLS SRS

Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single with 2-14" Venting Sidelites - Wide Mullion - 6/6, 6/8, 8/0

Single with Venting Sidelites - Wide Mullion

Brickmould Dim.	63 7/16"	65 7/16"	67 7/16"	69 7/16"	71 7/16"
Rough Opening	61 11/16"	63 11/16"	65 11/16"	67 11/16"	69 11/16"
Unit Dimension	60 15/16"	62 15/16"	64 15/16"	66 15/16"	68 15/16"



*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
S	Sidelite

Inswing



SLS SRS

French with 2-12" Venting Sidelites - Wide Mullion - 6/6, 6/8, 8/0

French with Venting Sidelites - Wide Mullion

Brickmould Dim.			88 1/8"	92 1/8"	96 1/8"	100 1/8"	104 1/8"
	Rough Opening		86 3/8"	90 3/8"	94 3/8"	98 3/8"	102 3/8"
		Unit Dimension	85 5/8"	89 5/8"	93 5/8"	97 5/8"	101 5/8"
80 1/2"	79 3/4"	79 1/4"	6/6				
			4/8	5/0	5/4	5/8	6/0
82 7/8"	82"	81 5/8"	6/8				
			4/8	5/0	5/4	5/8	6/0
98 7/8"	98"	97 5/8"	8/0				
			4/8	5/0	5/4	5/8	6/0

*Outswing not available

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
S	Sidelite

Inswing



SLAS



SARS

Unit and Rough Opening Sizing

THERMA-TRU® DOORS

French with 2-14" Venting Sidelites - Wide Mullion 6/6, 6/8, 8/0

French with Venting Sidelites - Wide Mullion

Brickmould Dim.	92 1/8"	96 1/8"	100 1/8"	104 1/8"	108 1/8"
Rough Opening	90 3/8"	94 3/8"	98 3/8"	102 3/8"	106 3/8"
Unit Dimension	89 5/8"	93 5/8"	97 5/8"	101 5/8"	105 5/8"



*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
S	Sidelite

Inswing



SLAS



SARS

Single Transoms

Unit Dimension	37 5/8"	13 1/2"	15 1/2"
13 7/16"	3/0	12"	14"

*Add actual unit dimension to door rough opening height for total rough opening height.

Double - Standard Continuous Mullion Transoms

Unit Dimension	62 13/16"	66 13/16"	70 13/16"	74 13/16"
13 7/16"	5/0	5/4	5/8	6/0
13 5/8"	5/0	5/4	5/8	6/0

*Add actual unit dimension to door rough opening height for total rough opening height.

Single with 2 Sidelites - Boxed Transoms

Unit Dimension	64 21/32"	68 21/32"
13 15/32"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL
13 5/8"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL
33 5/16"	3/0 w/ 2-12" SL	
35 5/16"		3/0 w/ 2-14" SL

*Add actual unit dimension to door rough opening height for total rough opening height.

Single with 2 Sidelites - Continuous Transoms

Unit Dimension	63 21/32"	67 21/32"
13 15/32"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL
13 5/8"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL
32 13/16"	3/0 w/ 2-12" SL	
34 13/16"		3/0 w/ 2-14" SL

*Add actual unit dimension to door rough opening height for total rough opening height.

Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single - 90 min. Fire Doors with Adjusta-Fit 2 Frames - 6/8, 7/0

Single

	2/0	2/4	2/6	2/8	2/10	3/0	3/6
Masonary R.O.	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"
Drywall R.O.	25"	29"	31"	33"	35"	37"	43"
Unit Dimension	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"

Height	Masonary R.O. Inswing	Drywall R.O. Inswing	Unit Dimension Inswing	Unit Dim. No Sill	Unit Dim. Public Access	Drywall R.O. No Sill	Drywall R.O. Public Access	Masonary R.O. No Sill	Masonary R.O. Public Access
6/8	82 11/32"	81 1/4"	82 11/32"	81 7/32"	82 21/32"	80 1/8"	80 5/8"	81 7/32"	82 21/32"
7/0	86 11/32"	85 1/4"	86 11/32"	85 7/32"	86 21/32"	84 1/8"	84 5/8"	85 7/32"	86 21/32"



	2/0	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"
Drywall R.O.	25"	29"	31"	33"	35"	37"	43"
Masonary R.O.	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"

Single



HORIZONTAL SECTION
(Fire Door)



VERTICAL SECTION
(Fire Door)