Unit and Rough Opening Sizing

Single or M.E.U. - 6/6, 6/8, 7/0, 8/0

Single or M.E.U. - Inswing

Brickmould Dim.	28"	32"	34"	36"	38"	40"	46"
Rough Opening	26 1/4"	30 1/4"	32 1/4"	34 1/4"	36 1/4"	38 1/4"	44 1/4"
Unit Dimension	25 1/2"	29 1/2"	31 1/2"	33 1/2"	35 1/2"	37 1/2"	43 1/2"



Unit Dim.	25 1/2"	29 1/2"	31 1/2"	33 1/2"	35 1/2"	37 1/2"	43 1/2"
Rough Opening	26 1/4"	30 1/4"	32 1/4"	34 1/4"	36 1/4"	38 1/4"	44 1/4"
Brickmould Dim.	28 1/2"	32 1/2"	34 1/2"	36 1/2"	38 1/2"	40 1/2"	46 1/2"

Composite	Aluminum	Composite	Aluminum	Composite	Aluminum
78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For M.E.U., add actual unit dimension to door rough opening width for total rough opening width.

For units with public access sills, subtract 13/16" from inswing height. Unit widths will be the same as in the table above.

Single or M.E.U. - Outswing

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

F L R

Outswing

F L R

Unit and Rough Opening Sizing

French - 7/8" Astragal - 6/6, 6/8, 7/0, 8/0

French - Inswing - Astragal

Widths	4/0	4/8	5/0	5/4	5/8	6/0
Brickmould Dim.	52 11/16"	60 11/16"	64 11/16"	68 11/16"	72 11/16"	76 11/16"
Rough Opening	50 15/16"	58 15/16"	62 15/16"	66 15/16"	70 15/16"	74 15/16"
Unit Dimension	50 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	74 3/16"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



French - Outswing - Astragal

Widths	4/0	4/8	5/0	5/4	5/8	6/0
Unit Dim.	50 3/16"	58 3/16"	62 3/16"	66 3/16"	70 3/16"	74 3/16"
Rough Opening	50 15/16"	58 15/16"	62 15/16"	66 15/16"	70 15/16"	74 15/16"
Brickmould Dim.	53 3/16"	61 3/16"	65 3/16"	69 3/16"	73 3/16"	77 3/16"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For units with public access sills, subtract 13/16" from inswing height. Unit widths will be the same as in the table above.

Hand Designations
(Viewed from the exterior)

A	Astragal (Passive)
L	Left Hand
R	Right Hand

Inswing


LA


AR

Outswing


AL

RA

Unit and Rough Opening Sizing

Double - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Double - Inswing - Standard Mullion

Brickmould Dim.	53"	61"	65"	69"	73"	77"
Rough Opening	51 1/4"	59 1/4"	63 1/4"	67 1/4"	71 1/4"	75 1/4"
Unit Dimension	50 1/2"	58 1/2"	62 1/2"	66 1/2"	70 1/2"	74 1/2"



Double - Outswing - Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FF LF RF FL FR

Outswing

FF LF RF FL FR

Unit and Rough Opening Sizing

THERMA TRU DOORS

Double - Wide Mullion - 6/6, 6/8, 7/0, 8/0

Double - Inswing - Wide Mullion

Brickmould Dim.	53 1/2"	61 1/2"	65 1/2"	69 1/2"	73 1/2"	77 1/2"
Rough Opening	51 3/4"	59 3/4"	63 3/4"	67 3/4"	71 3/4"	75 3/4"
Unit Dimension	51"	59"	63"	67"	71"	75"



51"	59"	63"	67"	71"	75"	**Unit Dim.**
51 3/4"	59 3/4"	63 3/4"	67 3/4"	71 3/4"	75 3/4"	**Rough Opening**
54"	62"	66"	70"	74"	78"	**Brickmould Dim.**

Double - Outswing - Wide Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FF LF RF FL FR

Outswing

FF LF RF FL FR

Triple - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Triple - Inswing - Standard Mullion

Brickmould Dim.	78"	90"	96"	102"	108"	114"
Rough Opening	76 1/4"	88 1/4"	94 1/4"	100 1/4"	106 1/4"	112 1/4"
Unit Dimension	75 1/2"	87 1/2"	93 1/2"	99 1/2"	105 1/2"	111 1/2"

Height	Inswing Brickmould Dim.	Inswing Rough Opening	Inswing Unit Dimension	Outswing Unit Dim. (Composite)	Outswing Rough Opening (Composite)	Outswing Brickmould Dim. (Composite)
6/6	80 1/2"	79 3/4"	79 1/4"	78 5/8"	79 1/8"	80 1/8"
6/8	82 7/8"	82"	81 5/8"	80 15/16"	81 7/16"	82 7/16"
7/0	86 7/8"	86"	85 5/8"	84 15/16"	85 7/16"	86 7/16"
8/0	98 7/8"	98"	97 5/8"	96 15/16"	97 7/16"	98 7/16"



Unit Dim.	75 1/2"	87 1/2"	93 1/2"	99 1/2"	105 1/2"	111 1/2"
Rough Opening	76 1/4"	88 1/4"	94 1/4"	100 1/4"	106 1/4"	112 1/4"
Brickmould Dim.	78 1/2"	90 1/2"	96 1/2"	102 1/2"	108 1/2"	114 1/2"

Triple - Outswing - Standard Mullion

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

Triple - Wide Mullion - 6/6, 6/8, 7/0, 8/0

Triple - Inswing - Wide Mullion

Brickmould Dim.	79"	91"	97"	103"	109"	115"
Rough Opening	77 1/4"	89 1/4"	95 1/4"	101 1/4"	107 1/4"	113 1/4"
Unit Dimension	76 1/2"	88 1/2"	94 1/2"	100 1/2"	106 1/2"	112 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Triple - Outswing - Wide Mullion

Unit Dim.	76 1/2"	88 1/2"	94 1/2"	100 1/2"	106 1/2"	112 1/2"
Rough Opening	77 1/4"	89 1/4"	95 1/4"	101 1/4"	107 1/4"	113 1/4"
Brickmould Dim.	79 1/2"	91 1/2"	97 1/2"	103 1/2"	109 1/2"	115 1/2"

Height	Unit Dim. (Composite)	Rough Opening (Composite)	Brickmould Dim. (Composite)
6/6	78 5/8"	79 1/8"	80 1/8"
6/8	80 15/16"	81 7/16"	82 7/16"
7/0	84 15/16"	85 7/16"	86 7/16"
8/0	96 15/16"	97 7/16"	98 7/16"

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

Single - Continuous with 10" Sidelite - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Standard Mullion

Brickmould Dim.	43"	45"	47"	49"	51"	57"
Rough Opening	41 1/4"	43 1/4"	45 1/4"	47 1/4"	49 1/4"	55 1/4"
Unit Dimension	40 1/2"	42 1/2"	44 1/2"	46 1/2"	48 1/2"	54 1/2"



80 1/2"	79 3/4"	79 1/4"	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"	Composite	Aluminum	Composite	Aluminum
82 7/8"	82"	81 5/8"	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"				
86 7/8"	86"	85 5/8"	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"				
98 7/8"	98"	97 5/8"	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"				

40 1/2"	42 1/2"	44 1/2"	46 1/2"	48 1/2"	54 1/2"	Unit Dim.
41 1/4"	43 1/4"	45 1/4"	47 1/4"	49 1/4"	55 1/4"	Rough Opening
43 1/2"	45 1/2"	47 1/2"	49 1/2"	51 1/2"	57 1/2"	Brickmould Dim.

Single with 1 Sidelite - Outswing - Continuous Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

LF RF FL FR

Outswing



LF RF FL FR

Unit and Rough Opening Sizing

Single - Continuous with 12" Sidelite - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	45"	47"	49"	51"	53"	59"
Rough Opening	43 1/4"	45 1/4"	47 1/4"	49 1/4"	51 1/4"	57 1/4"
Unit Dimension	42 1/2"	44 1/2"	46 1/2"	48 1/2"	50 1/2"	56 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 1 Sidelite - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	42 1/2"	44 1/2"	46 1/2"	48 1/2"	50 1/2"	56 1/2"
Rough Opening	43 1/4"	45 1/4"	47 1/4"	49 1/4"	51 1/4"	57 1/4"
Brickmould Dim.	45 1/2"	47 1/2"	49 1/2"	51 1/2"	53 1/2"	59 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Single - Continuous with 14" Sidelite - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	47"	49"	51"	53"	55"	61"
Rough Opening	45 1/4"	47 1/4"	49 1/4"	51 1/4"	53 1/4"	59 1/4"
Unit Dimension	44 1/2"	46 1/2"	48 1/2"	50 1/2"	52 1/2"	58 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 1 Sidelite - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	44 1/2"	46 1/2"	48 1/2"	50 1/2"	52 1/2"	58 1/2"
Rough Opening	45 1/4"	47 1/4"	49 1/4"	51 1/4"	53 1/4"	59 1/4"
Brickmould Dim.	47 1/2"	49 1/2"	51 1/2"	53 1/2"	55 1/2"	61 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

THERMA-TRU DOORS

Single - Continuous with 2-10" Sidelites - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	54"	56"	58"	60"	62"	68"
Rough Opening	52 1/4"	54 1/4"	56 1/4"	58 1/4"	60 1/4"	66 1/4"
Unit Dimension	51 1/2"	53 1/2"	55 1/2"	57 1/2"	59 1/2"	65 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Continuous Standard Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	51 1/2"	53 1/2"	55 1/2"	57 1/2"	59 1/2"	65 1/2"
Rough Opening	52 1/4"	54 1/4"	56 1/4"	58 1/4"	60 1/4"	66 1/4"
Brickmould Dim.	54 1/2"	56 1/2"	58 1/2"	60 1/2"	62 1/2"	68 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

Single - Continuous with 2-12" Sidelites - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Standard Mullion

		Brickmould Dim.	58"	60"	62"	64"	66"	72"					
		Rough Opening	56 1/4"	58 1/4"	60 1/4"	62 1/4"	64 1/4"	70 1/4"					
		Unit Dimension	55 1/2"	57 1/2"	59 1/2"	61 1/2"	63 1/2"	69 1/2"					
80 1/2"	79 3/4"	79 1/4"	6/6						78 5/8"	78 1/16"	79 1/8"	78 9/16"	79 9/16"
			2/4	2/6	2/8	2/10	3/0	3/6					
82 7/8"	82"	81 5/8"	6/8						80 15/16"	80 3/8"	81 7/16"	80 7/8"	81 7/8"
			2/4	2/6	2/8	2/10	3/0	3/6					
86 7/8"	86"	85 5/8"	7/0						84 15/16"	84 3/8"	85 7/16"	84 7/8"	85 7/8"
			2/4	2/6	2/8	2/10	3/0	3/6					
98 7/8"	98"	97 5/8"	8/0						96 15/16"	96 3/8"	97 7/16"	96 7/8"	97 7/8"
			2/4	2/6	2/8	2/10	3/0	3/6					
									Composite	**Aluminum**	**Composite**	**Aluminum**	**Aluminum**
			55 1/2"	57 1/2"	59 1/2"	61 1/2"	63 1/2"	69 1/2"	**Unit Dim.**				
			56 1/4"	58 1/4"	60 1/4"	62 1/4"	64 1/4"	70 1/4"	**Rough Opening**				
			58 1/2"	60 1/2"	62 1/2"	64 1/2"	66 1/2"	72 1/2"	**Brickmould Dim.**				

Single with 2 Sidelites - Outswing - Continuous Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FLF

FRF

Outswing

FLF

FRF

Unit and Rough Opening Sizing

THERMA TRU DOORS

Single - Continuous with 2-14" Sidelites - Standard Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Continuous Standard Mullion

Brickmould Dim.	62"	64"	66"	68"	70"	76"
Rough Opening	60 1/4"	62 1/4"	64 1/4"	66 1/4"	68 1/4"	74 1/4"
Unit Dimension	59 1/2"	61 1/2"	63 1/2"	65 1/2"	67 1/2"	73 1/2"



Aluminum	Composite	Aluminum	Composite	Aluminum	Composite
79 9/16"	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"
81 7/8"	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"
85 7/8"	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"
97 7/8"	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"

Unit Dim.	59 1/2"	61 1/2"	63 1/2"	65 1/2"	67 1/2"	73 1/2"
Rough Opening	60 1/4"	62 1/4"	64 1/4"	66 1/4"	68 1/4"	74 1/4"
Brickmould Dim.	62 1/2"	64 1/2"	66 1/2"	68 1/2"	70 1/2"	76 1/2"

Single with 2 Sidelites - Outswing - Continuous Standard Mullion

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FLF

FRF

Outswing

FLF

FRF

Single with 10" Sidelite - Boxed or Continuous Mullion Wide - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Boxed or Continuous Wide Mullion

Brickmould Dim.	Rough Opening	Unit Dimension	Height	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.				43 1/2"	45 1/2"	47 1/2"	49 1/2"	51 1/2"	57 1/2"
	Rough Opening			41 3/4"	43 3/4"	45 3/4"	47 3/4"	49 3/4"	55 3/4"
		Unit Dimension		41"	43"	45"	47"	49"	55"
80 1/2"	79 3/4"	79 1/4"	6/6	2/4	2/6	2/8	2/10	3/0	3/6
82 7/8"	82"	81 5/8"	6/8	2/4	2/6	2/8	2/10	3/0	3/6
86 7/8"	86"	85 5/8"	7/0	2/4	2/6	2/8	2/10	3/0	3/6
98 7/8"	98"	97 5/8"	8/0	2/4	2/6	2/8	2/10	3/0	3/6

Single with 1 Sidelite - Outswing - Boxed or Continuous Wide Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	41"	43"	45"	47"	49"	55"
Rough Opening	41 3/4"	43 3/4"	45 3/4"	47 3/4"	49 3/4"	55 3/4"
Brickmould Dim.	44"	46"	48"	50"	52"	58"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations (3/0 only):
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with one 10" sidelite and one mullion spread 3/4"would be: 49" unit size + 3/4" spread = 49 3/4"
Units can be spread 0" to 3" in 1/4" increments.
Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



Outswing



Unit and Rough Opening Sizing

Single with 12" Sidelite - Boxed or Continuous Wide Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Boxed or Continuous Wide Mullion

Brickmould Dim.	Rough Opening	Unit Dimension	Height	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.				45 1/2"	47 1/2"	49 1/2"	51 1/2"	53 1/2"	59 1/2"
	Rough Opening			43 3/4"	45 3/4"	47 3/4"	49 3/4"	51 3/4"	57 3/4"
		Unit Dimension		43"	45"	47"	49"	51"	57"
80 1/2"	79 3/4"	79 1/4"	6/6						
82 7/8"	82"	81 5/8"	6/8						
86 7/8"	86"	85 5/8"	7/0						
98 7/8"	98"	97 5/8"	8/0						

Single with 1 Sidelite - Outswing - Boxed or Continuous Wide Mullion

Height	2/4	2/6	2/8	2/10	3/0	3/6	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
Unit Dim.	43"	45"	47"	49"	51"	57"						
Rough Opening	43 3/4"	45 3/4"	47 3/4"	49 3/4"	51 3/4"	57 3/4"						
Brickmould Dim.	46"	48"	50"	52"	54"	60"						
6/6							78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8							80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0							84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0							96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations (3/0 only):
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with one 12" sidelite and one mullion spread 3/4"would be: 51" unit size + 3/4" spread = 51 3/4"
Units can be spread 0" to 3" in 1/4" increments.
Spread mullion only available in 3/0 inswing.

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



LF RF FL FR

Outswing



LF RF FL FR

Single with 14" Sidelite - Boxed or Continuous Wide Mullion - 6/6, 6/8, 7/0, 8/0

Single with 1 Sidelite - Inswing - Boxed or Continuous Wide Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	47 1/2"	49 1/2"	51 1/2"	53 1/2"	55 1/2"	61 1/2"
Rough Opening	45 3/4"	47 3/4"	49 3/4"	51 3/4"	53 3/4"	59 3/4"
Unit Dimension	45"	47"	49"	51"	53"	59"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 1 Sidelite - Outswing - Boxed or Continuous Wide Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	45"	47"	49"	51"	53"	59"
Rough Opening	45 3/4"	47 3/4"	49 3/4"	51 3/4"	53 3/4"	59 3/4"
Brickmould Dim.	48"	50"	52"	54"	56"	62"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations (3/0 only):
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with one 14" sidelite and one mullion spread 3/4"would be: 53" unit size + 3/4" spread = 53 3/4"
Units can be spread 0" to 3" in 1/4" increments.
Spread mullion only available in 3/0 inswing.

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



LF RF FL FR

Outswing



LF RF FL FR

Unit and Rough Opening Sizing

Single with 2-10" Sidelites - Boxed or Continuous Wide Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Boxed or Continuous Wide Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	55"	57"	59"	61"	63"	69"
Rough Opening	53 1/4"	55 1/4"	57 1/4"	59 1/4"	61 1/4"	67 1/4"
Unit Dimension	52 1/2"	54 1/2"	56 1/2"	58 1/2"	60 1/2"	66 1/2"

Height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"



Single with 2 Sidelites - Outswing - Boxed or Continuous Wide Mullion

	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	52 1/2"	54 1/2"	56 1/2"	58 1/2"	60 1/2"	66 1/2"
Rough Opening	53 1/4"	55 1/4"	57 1/4"	59 1/4"	61 1/4"	67 1/4"
Brickmould Dim.	55 1/2"	57 1/2"	59 1/2"	61 1/2"	63 1/2"	69 1/2"

Height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations (3/0 only):

Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with two 10" sidelites and two mullions spread 3/4" each would be: 60 1/2" unit size + 3/4" spread + 3/4" spread = 62"
Units can be spread 0" to 3" per mullion in 1/4" increments. (0" to 6" per unit in 1/2" increments).
Spread mullion only available in 3/0 inswing.

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



FLF FRF

Outswing



FLF FRF

Unit and Rough Opening Sizing

Single with 2-12" Sidelites - Boxed or Continuous Wide Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Boxed or Continuous Wide Mullion

Brickmould Dim.	59"	61"	63"	65"	67"	73"
Rough Opening	57 1/4"	59 1/4"	61 1/4"	63 1/4"	65 1/4"	71 1/4"
Unit Dimension	56 1/2"	58 1/2"	60 1/2"	62 1/2"	64 1/2"	70 1/2"



80 1/2"	79 3/4"	79 1/4"	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"	Unit Dim.	Composite	Aluminum	Composite
82 7/8"	82"	81 5/8"	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"	Rough Opening	Aluminum	Composite	Aluminum
86 7/8"	86"	85 5/8"	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"	Brickmould Dim.	Composite	Aluminum	Composite
98 7/8"	98"	97 5/8"	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"				

Single with 2 Sidelites - Outswing - Boxed or Continuous Wide Mullion

For Spread Mullion Configurations (3/0 only):
Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with two 12" sidelites and two mullions spread 3/4" each would be: 64 1/2" unit size + 3/4" spread + 3/4" spread = 66"
Units can be spread 0" to 3" per mullion in 1/4" increments. (0" to 6" per unit in 1/2" increments).
Spread mullion only available in 3/0 inswing.

Hand Designations
(Viewed from the exterior)

F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing

FLF

FRF

Outswing

FLF

FRF

Unit and Rough Opening Sizing

Single with 2-14" Sidelites - Boxed or Continuous Wide Mullion - 6/6, 6/8, 7/0, 8/0

Single with 2 Sidelites - Inswing - Boxed or Continuous Wide Mullion

Door width	2/4	2/6	2/8	2/10	3/0	3/6
Brickmould Dim.	63"	65"	67"	69"	71"	77"
Rough Opening	61 1/4"	63 1/4"	65 1/4"	67 1/4"	69 1/4"	75 1/4"
Unit Dimension	60 1/2"	62 1/2"	64 1/2"	66 1/2"	68 1/2"	74 1/2"

Door height	Brickmould Dim.	Rough Opening	Unit Dimension
6/6	80 1/2"	79 3/4"	79 1/4"
6/8	82 7/8"	82"	81 5/8"
7/0	86 7/8"	86"	85 5/8"
8/0	98 7/8"	98"	97 5/8"

Single with 2 Sidelites - Outswing - Boxed or Continuous Wide Mullion

Door width	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	60 1/2"	62 1/2"	64 1/2"	66 1/2"	68 1/2"	74 1/2"
Rough Opening	61 1/4"	63 1/4"	65 1/4"	67 1/4"	69 1/4"	75 1/4"
Brickmould Dim.	63 1/2"	65 1/2"	67 1/2"	69 1/2"	71 1/2"	77 1/2"

Door height	Unit Dim. Composite	Unit Dim. Aluminum	Rough Opening Composite	Rough Opening Aluminum	Brickmould Dim. Composite	Brickmould Dim. Aluminum
6/6	78 5/8"	78 1/16"	79 1/8"	78 9/16"	80 1/8"	79 9/16"
6/8	80 15/16"	80 3/8"	81 7/16"	80 7/8"	82 7/16"	81 7/8"
7/0	84 15/16"	84 3/8"	85 7/16"	84 7/8"	86 7/16"	85 7/8"
8/0	96 15/16"	96 3/8"	97 7/16"	96 7/8"	98 7/16"	97 7/8"

For Spread Mullion Configurations (3/0 only):

Add the total spread amount to width listed. For example, the unit size of a 3/0 unit with two 14" sidelites and two mullions spread 3/4" each would be: 68 1/2" unit size + 3/4" spread + 3/4" spread = 70"
Units can be spread 0" to 3" per mullion in 1/4" increments. (0" to 6" per unit in 1/2" increments).
Spread mullion only available in 3/0 inswing.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel
L	Left Hand
R	Right Hand

Inswing



FLF FRF

Outswing



FLF FRF

Sidelite - 6/6, 6/8, 7/0, 8/0

Sidelite - Inswing

Rough Opening		*	*	*
	Unit Dimension	11 1/2"	13 1/2"	15 1/2"
79 3/4"	79 1/4"			
	6/6	10"	12"	14"
82"	81 5/8"			
	6/8	10"	12"	14"
86"	85 5/8"			
	7/0	10"	12"	14"
98"	97 5/8"			
	8/0	10"	12"	14"

Unit Dim.	11 1/2"	13 1/2"	15 1/2"
Rough Opening	*	*	*

Composite	Aluminum	Composite	Aluminum
78 5/8"	78 1/16"	79 1/8"	78 9/16"
80 15/16"	80 3/8"	81 7/16"	80 7/8"
84 15/16"	84 3/8"	85 7/16"	84 7/8"
96 15/16"	96 3/8"	97 7/16"	96 7/8"

Sidelite - Outswing

*Add actual unit dimension to door rough opening width for total rough opening width.

Hand Designations (Viewed from the exterior)	
F	Fixed Panel

Inswing

F

Outswing

F

Unit and Rough Opening Sizing

Single with 12" Venting Sidelite - Wide Mullion - 6/6, 6/8

Single with Venting Sidelite - Wide Mullion

Brickmould Dim.		53 3/4"
	Rough Opening	52"
		Unit Dimension 51 1/4"

80 1/2"	79 3/4"	79 1/4"	6/6  3/0
82 7/8"	82"	81 5/8"	6/8  3/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
S	Vented Sidelite (hinged off jamb)

Inswing

SL SR LS RS

Single with 14" Venting Sidelite - Wide Mullion - 6/6, 6/8, 8/0

Single with Venting Sidelite - Wide Mullion

Brickmould Dim.			55 3/4"	
	Rough Opening		54"	
		Unit Dimension	53 1/4"	
80 1/2"	79 3/4"	79 1/4"	6/6	 3/0
82 7/8"	82"	81 5/8"	6/8	 3/0
98 7/8"	98"	97 5/8"	8/0	 3/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
S	Vented Sidelite (hinged off jamb)

Inswing


SL

SR

LS

RS

Unit and Rough Opening Sizing

THERMA-TRU® DOORS

Single with 2-12" Venting Sidelites - Wide Mullion - 6/6, 6/8

Single with Venting Sidelites - Wide Mullion

Brickmould Dim.		67 7/16"
	Rough Opening	65 11/16"
		Unit Dimension 64 15/16"

80 1/2"	79 3/4"	79 1/4"	6/6  3/0
82 7/8"	82"	81 5/8"	6/8  3/0

*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
S	Sidelite

Inswing



SLS SRS

Single with 2-14" Venting Sidelites - Wide Mullion - 6/6, 6/8, 8/0

Single with Venting Sidelites - Wide Mullion

Brickmould Dim.		71 7/16"
	Rough Opening	69 11/16"
		Unit Dimension
80 1/2"	79 3/4"	79 1/4"
82 7/8"	82"	81 5/8"
98 7/8"	98"	97 5/8"

6/6



3/0

6/8



3/0

8/0



3/0

*Outswing not available.

Hand Designations
(Viewed from the exterior)

L	Left Hand
R	Right Hand
S	Sidelite

Inswing

SLS

SRS

Unit and Rough Opening Sizing

THERMA-TRU DOORS

French with 2-12" Venting Sidelites - Wide Mullion - 6/6, 6/8

French with Venting Sidelites - Wide Mullion

		Brickmould Dim.	100 1/8"	104 1/8"
		Rough Opening	98 3/8"	102 3/8"
		Unit Dimension	97 5/8"	101 5/8"
80 1/2"	79 3/4"	79 1/4"	6/6	
82 7/8"	82"	81 5/8"	6/8	



*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
S	Sidelite

Inswing



SLAS



SARS

French with 2-14" Venting Sidelites - Wide Mullion - 6/6, 6/8, 8/0

French with Venting Sidelites - Wide Mullion

Brickmould Dim.			104 1/8"	108 1/8"
	Rough Opening		102 3/8"	106 3/8"
		Unit Dimension	101 5/8"	105 5/8"
80 1/2"	79 3/4"	79 1/4"	6/6	
82 7/8"	82"	81 5/8"	6/8	
98 7/8"	98"	97 5/8"	8/0	



*Outswing not available.

Hand Designations (Viewed from the exterior)	
L	Left Hand
R	Right Hand
A	Astragal
S	Sidelite

Inswing



SLAS



SARS

Unit and Rough Opening Sizing

Single Transoms

Unit Dimension	37 5/8"	13 1/2"	15 1/2"
13 15/32"	3/0	12"	14"

*Add actual unit dimension to door rough opening height for total rough opening height.

Double - Standard Continuous Mullion Transoms

Unit Dimension	62 13/16"	66 13/16"	70 13/16"	74 13/16"
13 15/32"	5/0	5/4	5/8	6/0
13 5/8"	5/0	5/4	5/8	6/0

*Add actual unit dimension to door rough opening height for total rough opening height.

Single with 2 Sidelites - Boxed Transoms

Unit Dimension	64 21/32"	68 21/32"
13 15/32"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL
13 5/8"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL

*Add actual unit dimension to door rough opening height for total rough opening height.

Single with 2 Sidelites - Continuous Transoms

Unit Dimension	63 21/32"	67 21/32"
13 15/32"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL
13 5/8"	3/0 w/ 2-12" SL	3/0 w/ 2-14" SL

*Add actual unit dimension to door rough opening height for total rough opening height.

Single - 90 min. Fire Doors with Adjusta-Fit 2 Frames - 6/8, 7/0

Single

	2/0	2/4	2/6	2/8	2/10	3/0	3/6
Masonry R.O.	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"
Drywall R.O.	25"	29"	31"	33"	35"	37"	43"
Unit Dimension	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"

Height	Masonry R.O. Inswing	Drywall R.O. Inswing	Unit Dimension Inswing	Unit Dim. No Sill	Unit Dim. Public Access	Drywall R.O. No Sill	Drywall R.O. Public Access	Masonry R.O. No Sill	Masonry R.O. Public Access
6/8	82 11/32"	81 1/4"	82 11/32"	81 7/32"	81 23/32"	80 1/8"	80 5/8"	81 7/32"	81 23/32"
7/0	86 11/32"	85 1/4"	86 11/32"	85 7/32"	85 23/32"	84 1/8"	84 5/8"	85 7/32"	85 23/32"



	2/0	2/4	2/6	2/8	2/10	3/0	3/6
Unit Dim.	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"
Drywall R.O.	25"	29"	31"	33"	35"	37"	43"
Masonry R.O.	27 1/4"	31 1/4"	33 1/4"	35 1/4"	37 1/4"	39 1/4"	45 1/4"

Single



HORIZONTAL SECTION
(Fire Door)



VERTICAL SECTION
(Fire Door)

This Page Intentionally Left Blank.