

# SUPER STEP®



Stepping is manufactured from our 47# Industrial Particleboard. Engineered for Interior Use Only.

## THICKNESS RANGE

1-1/8" Only

## DESCRIPTION

An engineered composite wood product cut into strips of standard widths and lengths with one long edge bullnosed.

## SPECIFICATION CONFORMANCE

Physical and Mechanical Properties are averages from normal product runs.

### Boise Cascade Particleboard complies with:

EPA TSCA Title VI, HUD 24 CFR 3280, CCR 93120 CARB ATCM Phase 2, CAN/CSA-0160-16 (Formaldehyde Emissions)  
ECC CPA 4-11 (Sustainability); ANSI A208.1 2016 (Physical Properties)  
Flame spread rating is Class C (International Code Council – International Fire Code® and National Fire Protection Association 101 Life Safety Code®) as tested to ASTM E84 and CAN/ULC-S102-10.

MANUFACTURING STANDARDS <i>Average</i>	IMPERIAL	METRIC (SI)
Density	47.0 lb/ft <sup>3</sup>	0.753 g/cm <sup>3</sup>
Internal Bond	115 psi	0.793 N/mm <sup>2</sup>
Screw Holding - Face	310 lbs	1,379 N
Screw Holding - Edge	190 lbs	845.2 N
Formaldehyde, Emissions (TSCA Title VI)	< 0.09 ppm	< 0.09 ppm
Linear Expansion - Maximum	0.35%	0.35%
Water Absorption - Maximum	20%	20%
Moisture Content	7%	7%
Sanding	100 grit	-

SHIPPING DATA	IMPERIAL	METRIC (SI)
Thickness - <i>Nominal</i>	1-1/8 inches	28.5 mm
Weight / MSF	4,406 lbs	1,999 kg
Packaging - <i>Pieces per Unit</i>	56 pcs (4 wide by 14 high)	
Width - <i>Standard</i> (inquire if special width is needed)	11-1/4 inches	
Length - <i>Standard</i> (inquire if special length is needed)	8', 10', 12'	

### PLEASE NOTE:

- SUPER STEP®** brand stair tread is for interior application only. It should be kept dry during storage and construction.
- SUPER STEP®** brand stair tread shall be covered with carpeting or other finish flooring material.
- SUPER STEP®** brand stair tread shall be installed using conventional framing and fastening practices that are in compliance with all applicable code requirements. In addition, structural adhesives must be used in combination with nailing.
- Stairs where entries may be subject to wet foot traffic should have the treads protected with a waterproof wearing surface such as linoleum or vinyl floor covering. When carpeting is used in these areas, the tread shall be protected with suitable moisture-resistant coating before installation of carpet.



For more information, including sales terms and conditions, visit our website at: [www.bc.com/particleboard](http://www.bc.com/particleboard)  
Email: [TWParticleboardSales@BC.com](mailto:TWParticleboardSales@BC.com)  
Phone: 888-264-7372



All products are available SFI®  
Chain-of-Custody Certified.